

Model(s)
 Model Year
 Limbs
 Cable Guard Bar
 Limb Bolt Length

PowerTec II Carbonite Target & Hunting
 1999
 4 Piece Laminated Carbon (16")
 High Short
 2.5

Date 2-Nov-98
 Revision

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC	75%	6 3/8	37 3/4	24	2	A	52.75	39.25
	75%	6 3/8	37 3/4	25	2	C	52.75	39.25
P2NHC	75%	6 3/8	37 3/4	26	2	E	52.75	39.25
P2N2C	75%	6 3/8	37 3/4	27	2	G	52.75	39.25
	75%	6 3/8	37 3/4	28	3	C	56.25	39.75
	75%	6 3/8	37 3/4	29	3	E	56.25	39.75
	75%	6 3/8	37 3/4	30	3	G	56.25	39.75
	75%	6 3/4	37 1/8	31	4	F	57.75	39.25
	75%	6 3/4	37 1/8	32	4	H	57.75	39.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC	65%	6 3/8	37 3/4	24	2	A	52.75	39.25
	65%	6 3/8	37 3/4	25	2	C	52.75	39.25
P2NHD	65%	6 3/8	37 3/4	26	2	E	52.75	39.25
P2N2D	65%	6 3/8	37 3/4	27	2	G	52.75	39.25
	65%	6 3/8	37 3/4	28	3	C	56.25	39.75
	65%	6 3/8	37 3/4	29	3	E	56.25	39.75
	65%	6 3/8	37 3/4	30	3	G	56.25	39.75
	65%	6 3/4	37 1/8	31	4	F	57.75	39.25
	65%	6 3/4	37 1/8	32	4	H	57.75	39.25

	Letoff %	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
PW	65/75	6 3/4	35 7/8	24	2	A	50.75	37.75
	65/75	6 3/4	35 7/8	25	2	C	50.75	37.75
P2NHW/V P2N2W/V	65/75	6 3/4	35 7/8	26	2	E	50.75	37.75
	65/75	6 3/4	36	27	3	B	54.25	38.25
	65/75	6 3/4	36	28	3	D	54.25	38.25
	65/75	6 3/4	36	29	3	F	54.25	38.25
	65/75	6 3/4	36 1/8	30	4	E	56.25	38.75
	65/75	6 3/4	36 1/8	31	4	G	56.25	38.75
	65/75	6 3/4	36 1/8	32	4	H	56.25	38.75

W = 65%, V = 75%

Letoff, brace height, axle to axle length given as a general production guide only

Desc: TUNE/DEFLECTION CHART - POWERTEC CARBONITE HUNTING & TARGET
 File: P2 - TUNE: P2 CARBONITE DATE: 2-Nov-98
 HOYT USA