

Model(s) **TurboTec**
 Model Year **2005**
 Limbs **XT2000**
 Cable Guard Bar **7 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **#27&28**

Date **3/28/2005**

Revision **A**

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	5 5/8	35 1/2	24	E	A	48.5	39.5	37.25
	65/75	5 5/8	35 1/2	25	E	B	49.5	39.75	37.5
	65/75	5 7/8	35 1/4	26	E	C	50.5	39.75	37.25
	65/75	6	35 1/2	27	E	D	52	40.25	37.5
	65/75	6 1/8	35 1/2	28	E	E	53	40.25	37.5
	65/75	6 1/8	35 5/8	29	E	F	54.5	40.75	37.75
	65/75	6 1/8	35 7/8	30	E	G	56	41.5	38

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
spiral cam & 1/2	65%	5 3/4	35	23	1.0	53	39.5	37
	65%	5 3/4	35	23.5	1.5	53	39.5	37
	65%	5 3/4	35	24	2.0	53	39.5	37
	65%	5 3/4	35	24.5	2.5	53	39.5	37
	65%	6	34 3/8	25	3.0	54.5	39.75	36.75
	65%	6	34 3/8	25.5	3.5	54.5	39.75	36.75
	65%	6	34 3/8	26	4.0	54.5	39.75	36.75
	65%	6 1/8	34 3/8	26.5	4.5	56	39.5	36.25
	65%	6 1/8	34 3/8	27	5.0	56	39.5	36.25
	65%	6 1/8	34 3/8	27.5	5.5	56	39.5	36.25
	65%	5 3/4	35 1/2	28	6.0	58.5	40.25	37.25
	65%	5 3/4	35 1/2	28.5	6.5	58.5	40.25	37.25
	65%	5 3/4	35 1/2	29	7.0	58.5	40.25	37.25
	65%	6 1/8	34 7/8	29.5	7.5	59.5	40.5	36.5
	65%	6 1/8	34 7/8	30	8.0	59.5	40.5	36.5