

Model(s) UltraTec
 Model Year 2006
 Limbs XT3000
 Cable Guard Bar 9 1/2
 Limb Bolt Length 2 1/2
 Pocket Triax #25 & #26

Date 12/8/2005

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	7 5/8	39 5/8	26	D	C&1/2 #1	52.5	43.5	41
cam	65/75	7 1/2	40 1/8	27	D	C&1/2 #2	54	44	41.75
& 1/2	65/75	7 5/8	40 1/8	28	D	C&1/2 #3	55	44.5	41.75
adjustable	65/75	7 5/8	40 1/8	29	D	C&1/2 #4	56.5	45	42.25
	65/75	7 9/16	40 1/4	30	D	C&1/2 #5	58.0	45.25	42.5
	65/75	7 11/16	40 5/8	31	D	C&1/2 #6	59.5	45.75	42.75
	65/75	7 3/4	40 3/4	32	D	C&1/2 #7	61	46.5	43

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	7 3/8	39 1/2	26	1.0	57.5	44	41.25
	65%	7 3/8	39 1/2	26 1/2	1.5	57.5	44	41.25
	65%	7 3/8	39 1/2	27	2.0	57.5	44	41.25
	65%	7 3/8	39 1/2	27 1/2	2.5	57.5	44	41.25
	65%	7 3/8	39 1/2	28	3.0	59.5	44.5	41.5
	65%	7 3/8	39 1/2	28 1/2	3.5	59.5	44.5	41.5
cam	65%	7 3/8	39 1/2	29	4.0	59.5	44.5	41.5
& 1/2	65%	7 1/2	39 1/2	29 1/2	4.5	61	44.5	41.25
spiral	65%	7 1/2	39 1/2	30	5.0	61	44.5	41.25
	65%	7 1/2	39 1/2	30 1/2	5.5	61	44.5	41.25
	65%	7 3/8	39 7/8	31	6.0	63	44.5	41.5
	65%	7 3/8	39 7/8	31 1/2	6.5	63	44.5	41.5
	65%	7 3/8	39 7/8	32	7.0	63	44.5	41.5
	65%	7 3/16	40 1/2	32 1/2	7.5	65	46	42
	65%	7 3/16	40 1/2	33	8.0	65	46	42

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	7 1/2	40	24 1/2	0.0	56.5	44	41
	65%	7 1/2	40	25	0.5	56.5	44	41
	65%	7 1/2	40	25 1/2	1.0	56.5	44	41
	65%	7 1/2	40	26	1.5	56.5	44	41
	65%	7 1/2	40	26 1/2	2.0	56.5	44	41
	65%	7 1/2	40	27	2.5	56.5	44.25	41
	65%	7 1/2	40	27 1/2	3.0	56.5	44.25	41
	65%	7 3/4	39 3/4	28	3.5	60	45.25	41.25
wheel	65%	7 3/4	39 3/4	28 1/2	4.0	60	45.25	41.25
& 1/2	65%	7 3/4	39 3/4	29	4.5	60	45.25	41.25
	65%	7 3/4	39 3/4	29 1/2	5.0	60	45.25	41.25
	65%	7 3/4	39 3/4	30	5.5	60	45.25	41.25
	65%	7 3/4	39 3/4	30 1/2	6.0	60	45.25	41.25
	65%	7 3/4	40 1/8	31	6.5	64.25	46.75	42
	65%	7 3/4	40 1/8	31 1/2	7.0	64.25	46.75	42
	65%	7 3/4	40 1/8	32	7.5	64.25	46.75	42
	65%	7 3/4	40 1/8	32 1/2	8.0	64.25	46.75	42