

Model(s) ProTec XT 3000 Hunting and Target
 Model Year 2002
 Limbs XT 3000 (15 1/2")
 Cable Guard Bar 10.50
 Limb Bolt Length 2.5
 Pocket 22/23

Date 5/17/2002
 Revision C

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65%	8 1/8	40 5/8	23	1	A	53.0	42.5
8 1/8		40 5/8	24	1	C	53.0	42.5	
8 1/8		40 5/8	25	1	F	53.0	42.5	
AccuWheel	65%	8 1/4	40 7/8	26	2	B	55.0	42.5
	65%	8 1/4	40 7/8	27	2	D	55.0	42.5
AW 2PT3H/T	65%	8 1/4	40 7/8	28	2	G	55.0	42.5
	65%	8 1/8	41 1/8	29	3	C	59.0	43.0
	65%	8 1/8	41 1/8	30	3	E	59.0	43.0
	65%	8 1/8	41 1/8	31	3	G	59.0	43.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65 / 75%	8 1/2	40 1/4	24	1	B	53.0	41.0
8 1/2		40 1/4	25	1	C	53.0	41.0	
Command CL/CH	65 / 75%	8 1/2	40 1/4	26	1	E	53.0	41.0
	65 / 75%	8 1/2	40 1/4	27	1	G	53.0	41.0
2PT3H/T	65 / 75%	8 3/4	40 5/8	28	2	D	56.0	41.5
	65 / 75%	8 3/4	40 5/8	29	2	F	56.0	41.5
	65 / 75%	8 3/4	40 5/8	30	2	H	56.0	41.5
	65 / 75%	8 3/4	41 1/4	31	3	D	60.5	42.0
	65 / 75%	8 3/4	41 1/4	32	3	F	60.5	42.0
	65 / 75%	8 7/8	41 1/4	33	4	F	62.5	42.0
	65 / 75%	8 7/8	41 1/4	34	4	H	62.5	42.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	DT String	CBC	YBC	
	60 / 75%	9 1/4	40 1/4	27.5	1	3.0	59.5	47.0	42.0	
9 1/4		40 1/4	28	1.5	3.0	59.5	47.0	42.0		
9 1/4		40 1/4	28.5	2	3.0	59.5	47.0	42.0		
9 1/4		40 1/4	29	2.5	3.0	59.5	47.0	42.0		
9 1/4		40 1/4	29.5	3	3.0	59.5	47.0	42.0		
9 1/4		40 1/4	30	3.5	3.0	59.5	47.0	42.0		
Excel EC		60 / 75%	9 3/8	40 1/2	30.5	4	4.0	62.0	48.0	42.5
		60 / 75%	9 3/8	40 1/2	31	4.5	4.0	62.0	48.0	42.5
2PT3H/T		60 / 75%	9 3/8	40 1/2	31.5	5	4.0	62.0	48.0	42.5
		60 / 75%	9 3/8	40 1/2	32	5.5	4.0	62.0	48.0	42.5
	60 / 75%	9 3/8	40 1/2	32.5	6	4.0	62.0	48.0	42.5	
	60 / 75%	9 3/8	40 1/2	33	6.5	5.0	64.5	48.5	43.0	
	60 / 75%	9 3/8	40 1/2	33.5	7	5.0	64.5	48.5	43.0	
	60 / 75%	9 3/8	40 1/2	34	7.5	5.0	64.5	48.5	43.0	

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	Module Position	DT String	CBC	YBC	
	60 / 75%	8 3/4	41 1/4	27 1/2	1	3.0	A-1	60.5	47.5	44.0	
8 3/4		41 1/4	28	1	3.0	C-3	60.5	47.5	44.0		
8 3/4		41 1/4	28 1/2	1	3.0	D-4	60.5	47.5	44.0		
8 3/4		41 1/4	29	1	3.0	E-5	60.5	47.5	44.0		
8 3/4		41 1/4	29 1/2	1	3.0	F-6	60.5	47.5	44.0		
9		41	30	2	4.0	B-2	63.0	48.0	44.0		
VersaCam VC		60 / 75%	9	41	30 1/2	2	4.0	C-3	63.0	48.0	44.0
		60 / 75%	9	41	31	2	4.0	D-4	63.0	48.0	44.0
2PT3H/T		60 / 75%	9	41	31 1/2	2	4.0	E-5	63.0	48.0	44.0
		60 / 75%	9	41	32	2	4.0	F-6	63.0	48.0	44.0
	60 / 75%	9	41	32 1/2	2	4.0	G-7	63.0	48.0	44.0	
60 / 75%	9	41	33	2	4.0	H-8	63.0	48.0	44.0		

Letoff, brace height, axle to axle length given as a general production guide only