

Prevail FX - XT2000 - SVX Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE
SVX	65%	6 1/2	33 13/16	23	A	1	52.25	39.38	35.88
	65%	6 1/2	33 13/16	23 1/2	B	1	52.25	39.38	35.88
	65%	6 1/2	33 13/16	24	*C	1	52.25	39.38	35.88
	65%	6 1/2	33 13/16	24 1/2	D	1	52.25	39.38	35.88
	65%	6 1/2	33 13/16	25	E	1	52.25	39.38	35.88
	65%	6 1/2	34 1/2	25 1/2	A	2	54.38	38.50	36.50
	65%	6 1/2	34 1/2	26	B	2	54.38	38.50	36.50
	65%	6 1/2	34 1/2	26 1/2	*C	2	54.38	38.50	36.50
	65%	6 1/2	34 3/8	27	A	3	56.00	38.38	36.00
	65%	6 1/2	34 3/8	27 1/2	B	3	56.00	38.38	36.00
	65%	6 1/2	34 3/8	28	*C	3	56.00	38.38	36.00
	65%	6 1/2	34 7/8	28 1/2	A	4	57.88	38.75	36.63
	65%	6 1/2	34 7/8	29	B	4	57.88	38.75	36.63
	65%	6 1/2	34 7/8	29 1/2	*C	4	57.88	38.75	36.63
	65%	6 1/2	35 1/4	30	A	5	59.75	39.25	36.88
	65%	6 1/2	35 1/4	30 1/2	*B	5	59.75	39.25	36.88

Prevail FX - XT2000 - X3 Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE
X3	65/75 %	6 3/4	33 5/8	23 1/2	A	1	51.25	37.13	35.63
	65/75 %	6 3/4	33 5/8	24	B	1	51.25	37.13	35.63
	65/75 %	6 3/4	33 5/8	24 1/2	C	1	51.25	37.13	35.63
	65/75 %	6 3/4	33 5/8	25	*D	1	51.25	37.13	35.63
	65/75 %	6 3/4	33 5/8	25 1/2	E	1	51.25	37.13	35.63
	65/75 %	6 13/16	34 3/16	25 1/2	A	2	54.63	37.63	36.25
	65/75 %	6 13/16	34 3/16	26	B	2	54.63	37.63	36.25
	65/75 %	6 13/16	34 3/16	26 1/2	C	2	54.63	37.63	36.25
	65/75 %	6 13/16	34 3/16	27	*D	2	54.63	37.63	36.25
	65/75 %	6 13/16	34 3/16	27 1/2	E	2	54.63	37.63	36.25
	65/75 %	6 13/16	35 1/8	27 1/2	A	3	57.63	38.38	36.88
	65/75 %	6 13/16	35 1/8	28	B	3	57.63	38.38	36.88
	65/75 %	6 13/16	35 1/8	28 1/2	C	3	57.63	38.38	36.88
	65/75 %	6 13/16	35 1/8	29	*D	3	57.63	38.38	36.88
	65/75 %	6 13/16	35 1/8	29 1/2	E	3	57.63	38.38	36.88

Model: Prevail Elite FX Bow Mount #3 Adjustable shot bar: 4.50 Pocket: W10 String Model: SVX-VX Date: 11/15/16
 Model Year: 2017 Bar Mount #2 Limb: XT2000 Rocker: #6 X3-VX2
 * = Shipped module position Limb Shox #3

Prevail FX SD - XT1000 - X3 Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE
X3	65/75 %	5 3/4	33 7/8	22 3/4	A	1	51.50	37.63	36.00
	65/75 %	5 3/4	33 7/8	23 1/4	B	1	51.50	37.63	36.00
	65/75 %	5 3/4	33 7/8	23 3/4	C	1	51.50	37.63	36.00
	65/75 %	5 3/4	33 7/8	24 1/3	*D	1	51.50	37.63	36.00
	65/75 %	5 3/4	33 7/8	24 3/4	E	1	51.50	37.63	36.00

Model: Prevail FX SD Bow Mount #3 Adjustable shot bar: 4.50 Pocket: W10 String Model: X3-VX2 Date: 11/15/16
 Model Year: 2017 Bar Mount #2 Limb: XT1000 Rocker: #6
 * = Shipped module position Limb Shox #3