

Model(s) MagnaTec XT 2000 Hunting
Model Year 2002
Limbs XT 2000 (14")
Cable Guard Bar 9.00
Limb Bolt Length 2.5
Pocket 17

Date 11/20/2001

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65 / 75%	6 5/8	35 1/4	21	1	A	48.5	36.5
	65 / 75%	6 5/8	35 1/4	22	1	D	48.5	36.5
	65 / 75%	6 5/8	35 1/4	23	1	F	48.5	36.5
Command	65 / 75%	6 1/2	35 3/4	24	2	B	51.5	37.0
CL/CH	65 / 75%	6 1/2	35 3/4	25	2	E	51.5	37.0
2MT2H	65 / 75%	6 1/2	35 3/4	26	2	G	51.5	37.0
	65 / 75%	6 5/8	36 1/4	27	3	B	55.5	37.0
	65 / 75%	6 5/8	36 1/4	28	3	E	55.5	37.0
	65 / 75%	6 5/8	36 1/4	29	3	G	55.5	37.0
	65 / 75%	6 3/4	36 3/8	30	4	E	58.5	37.0
	65 / 75%	6 3/4	36 3/8	31	4	G	58.5	37.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
	60 / 75%	7	35 1/8	24	1	A-1	3	54.0	41.5	38.0
	60 / 75%	7	35 1/8	25	1	C-3	3	54.0	41.5	38.0
	60 / 75%	7	35 1/8	26	1	E-5	3	54.0	41.5	38.0
Versa	60 / 75%	7	35 1/2	27	2	C-3	4	57.0	42.5	38.5
VC	60 / 75%	7	35 1/2	28	2	E-5	4	57.0	42.5	38.5
2MT2H	60 / 75%	7	35 1/2	29	2	G-7	4	57.0	42.5	38.5
	60 / 75%	7 3/8	35 1/2	30	3	D-4	5	60.5	43.5	39.0
	60 / 75%	7 3/8	35 1/2	31	3	F-6	5	60.5	43.5	39.0
	60 / 75%	7 3/8	35 1/2	32	3	H-8	5	60.5	43.5	39.0

Letoff, brace height, axle to axle length given as a general production guide only