

Model(s) AlphaTec Power Flex Hunting and Target
Model Year 1998
Limbs 4 Piece Flat Glass (16")
Cable Guard Bar AT Carb. Med
Limb Bolt Length 2.5
Physical Weight 5 lb

Date 20-Nov-97

Revision A

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	75%	7	39 1/8	25	2	A	54.5	35
	75%	7	39 1/8	26	2	C	54.5	35
CC	75%	7	39 1/8	27	2	E	54.5	35
ATPHC	75%	7	39 1/8	28	2	G	54.5	35
ATPTC	75%	7	39 1/8	29	3	C	58	35.5
	75%	7	39 1/8	30	3	E	58	35.5
	75%	7	39 1/8	31	3	G	58	35.5

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7	39 1/8	25	2	A	54.5	35
	65%	7	39 1/8	26	2	C	54.5	35
CC	65%	7	39 1/8	27	2	E	54.5	35
ATPHD	65%	7	39 1/8	28	2	G	54.5	35
ATPTD	65%	7	39 1/8	29	3	C	58	35.5
	65%	7	39 1/8	30	3	E	58	35.5
	65%	7	39 1/8	31	3	G	58	35.5

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7	39 1/8	25	2	A	55.5	35
	65%	7	39 1/8	26	2	C	55.5	35
PC	65%	7	39 1/8	27	2	E	55.5	35
ATPHP	65%	7	39 1/8	28	2	G	55.5	35
ATPTP	65%	7	39 1/8	29	3	C	59.5	35.5
	65%	7	39 1/8	30	3	E	59.5	35.5
	65%	7	39 1/8	31	3	G	59.5	35.5

Letoff, brace height, axle to axle length given as a general production guide only
THIS DATA SHEET VOID FOR PRODUCTION USE UNLESS RELEASE STAMP APPEARS IN RED

Desc: TUNE/DEFLECTION CHART - ALPHATEC POWER FLEX HUNTING AND TARGET

File: AT - TUNE: AT POWER FLEX DATE: 20-Nov-97

HOYT USA