

Model(s) Viper Carbonite Hunting & Target  
 Model Year 1999  
 Limbs 4 Piece Laminated Carbon (16")  
 Cable Guard Bar Hi. Medium  
 Limb Bolt Length 2.5

Date 2-Nov-98

Revision

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC VPNHC VPNTC	75%	5 5/8	35 3/4	23	2	A	50.75	37.25
	75%	5 5/8	35 3/4	24	2	C	50.75	37.25
	75%	5 5/8	35 3/4	25	2	E	50.75	37.25
	75%	5 5/8	35 3/4	26	2	G	50.75	37.25
	75%	5 5/8	36 1/4	27	3	C	54.75	38.25
	75%	5 5/8	36 1/4	28	3	E	55.75	38.26
	75%	5 5/8	36 1/4	29	3	G	56.75	38.27
	75%	5 1/2	36 3/8	30	4	G	56.75	38.75
	75%	5 1/2	36 3/8	31	4	H	56.75	38.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC VPNHD VPNTD	65%	5 5/8	35 3/4	23	2	A	50.75	37.25
	65%	5 5/8	35 3/4	24	2	C	50.75	37.25
	65%	5 5/8	35 3/4	25	2	E	50.75	37.25
	65%	5 5/8	35 3/4	26	2	G	50.75	37.25
	65%	5 5/8	36 1/4	27	3	C	54.75	38.25
	65%	5 5/8	36 1/4	28	3	E	54.75	38.25
	65%	5 5/8	36 1/4	29	3	G	54.75	38.25
	65%	5 1/2	36 3/8	30	4	G	56.75	38.75
	65%	5 1/2	36 3/8	31	4	H	56.75	38.75

	Letoff %	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
PW VPNHVV VPNTVV	65/75	5 1/2	35 3/8	23	2	B	50.25	37.25
	65/75	5 1/2	35 3/8	24	2	D	50.25	37.25
	65/75	5 1/2	35 3/8	25	2	F	50.25	37.25
	65/75	5 1/2	35 5/8	26	3	B	53.75	37.75
	65/75	5 1/2	35 5/8	27	3	D	53.75	37.75
	65/75	5 1/2	35 5/8	28	3	F	53.75	37.75
	65/75	5 1/2	35 3/4	29	4	F	55.75	38.25
	65/75	5 1/2	35 3/4	30	4	H	55.75	38.25
	65/75	5 1/2	35 3/4	31	4	H	55.75	38.25

W = 65%, V = 75%

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*

Desc: TUNE/DEFLECTION CHART - VIPER CARBONITE HUNTING & TARGET

File: VP - TUNE: VP CARBONITE DATE: 2-Nov-98

HOYT USA