

Model(s) **ProTec**
 Model Year **2005**
 Limbs **XT4000**
 Cable Guard Bar **10**
 Limb Bolt Length **2 1/2**
 Pocket **Triton #25&26**

Date **1/26/05**

Revision **B**

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	8 3/8	45 1/2	29	E	A	58.5	49.25	47
cam	65/75	8 1/2	45 1/2	30	E	B	59.5	49.75	47.5
& 1/2	65/75	8 5/8	45 1/2	31	E	C	60.5	49.75	47.25
adjustable	65/75	8 3/4	45 3/4	32	E	D	61.5	50	47.25
	65/75	8 3/4	45 1/2	33	E	E	63	50.25	47.5
	65/75	8 3/4	45 1/2	34	E	F	64.5	50.75	47.75
	65/75	8 3/4	45 3/4	35	E	G	66	51.5	48

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	9	44 3/4	27 1/2	0.0	61.5	48.75	45.75
	65%	9	44 3/4	28	0.5	61.5	48.75	45.75
	65%	9	44 3/4	28 1/2	1.0	61.5	48.75	45.75
	65%	9	44 3/4	29	1.5	61.5	48.75	45.75
	65%	9	44 3/4	29 1/2	2.0	61.5	48.75	45.75
	65%	9	44 3/4	30	2.5	61.5	49	45.75
	65%	9	44 3/4	30 1/2	3.0	61.5	49	45.75
	65%	9 1/8	44 1/2	31	3.5	65	50	46
wheel	65%	9 1/8	44 1/2	31 1/2	4.0	65	50	46
& 1/2	65%	9 1/8	44 1/2	32	4.5	65	50	46
	65%	9 1/8	44 1/2	32 1/2	5.0	65	50	46
	65%	9 1/8	45	33	6.0	69.5	51.5	46.75
	65%	9 1/8	45	33 1/2	6.5	69.5	51.5	46.75
	65%	9 1/8	45	34	7.0	69.5	51.5	46.75
	65%	9 1/8	45	34 1/2	7.5	69.5	51.5	46.75
	65%	9 1/8	45	35	8.0	69.5	51.5	46.75