

Model(s) ULTRATEC
Model Year 2003
Limbs XT3000
Cable Guard Bar 9.50
Limb Bolt Length 2.50
Pocket #22 or #23

Date 2/12/03

Revision E

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	BASE CAM	Module Position	String	YBC
Accuwheel AW	65%	7	40 1/8	22	1	A	52.5	42
	65%	7	40 1/8	23	1	D	52.5	42
	65%	7	40 1/8	24	1	F	52.5	42
	65%	7	40 3/8	25	2	C	54.5	42
	65%	7	40 3/8	26	2	F	54.5	42
	65%	7	41 5/8	27	3	B	58.5	42.5
	65%	7	41 5/8	28	3	D	58.5	42.5
	65%	7	41 5/8	29	3	F	58.5	42.5
	65%	7	41 5/8	30	3	H	58.5	42.5

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	CAM & MODULE	MODULE POSITION	STRING	HCBC	HYBC
Cam &1/2 Adjustable	65/75%	7 5/8	39 5/8	26	A-1	D	52.5	43.5	41.25
	65/75%	7 5/8	40 1/8	27	B-2	D	54.0	44.25	42.0
	65/75%	7 3/8	40 1/2	28	C-3	D	55.0	44.5	42.0
	65/75%	7 1/2	40 1/2	29	D-4	D	57.0	45.5	42.75
	65/75%	7 3/4	40 1/2	30	E-5	D	58.0	45.25	42.5
	65/75%	7 3/4	40 3/4	31	F-6	D	59.5	46.0	43.0
	65/75%	7 3/4	41	32	G-7	C	61.0	46.75	43.25

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	BASE CAM	STRING	HCBC	HYBC
Spiral Cam &1/2	65%	7 1/8	40 1/4	26	1	58.5	45.0	42.25
	65%	7 1/8	40 1/4	26.5	1.5	58.5	45.0	42.25
	65%	7 1/8	40 1/4	27	2	58.5	45.0	42.25
	65%	7 1/8	40 1/4	27.5	2.5	58.5	45.0	42.25
	65%	7 3/8	40	28	3	60.0	45.0	42.0
	65%	7 3/8	40	28.5	3.5	60.0	45.0	42.0
	65%	7 3/8	40	29	4	60.0	45.0	42.0
	65%	7 5/8	39 3/8	29.5	4.5	61.0	44.5	41.25
	65%	7 5/8	39 3/8	30	5	61.0	44.5	41.25
	65%	7 5/8	39 3/8	30.5	5.5	61.0	44.5	41.25
	65%	7 1/2	39 7/8	31	6	63.0	44.75	41.75
	65%	7 1/2	39 7/8	31.5	6.5	63.0	44.75	41.75
	65%	7 1/2	39 7/8	32	7	63.0	44.75	41.75
	65%	7 3/8	40 1/4	32.5	7.5	65.0	45.75	41.75
	65%	7 3/8	40 1/4	33	8	65.0	45.75	41.75