

Model(s) **ProTec**
 Model Year **2006**
 Limbs **XT3000**
 Cable Guard Bar **10**
 Limb Bolt Length **2 1/2**
 Pocket **27 & 28**

Date **12/8/2005**

Revision

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	8 1/8	41 1/8	27	D	C&1/2 #1	54	44.75	42.5
	65/75	8 5/16	40 7/8	28	D	C&1/2 #2	55	44.75	42.5
	65/75	8 3/8	41	29	D	C&1/2 #3	56	45.25	42.5
	65/75	8 9/16	40 1/4	30	D	C&1/2 #4	56.75	45.25	42.25
	65/75	8 9/16	40 5/8	31	D	C&1/2 #5	58.25	45.5	42.75
	65/75	8 11/16	40 5/8	32	D	C&1/2 #6	59.25	45.75	42.75
	65/75	8 7/8	40 3/4	33	D	C&1/2 #7	60.75	46.5	43

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	8 1/4	40	26 1/2	1.0	57.75	44.5	41.75
	65%	8 1/4	40	27	1.5	57.75	44.5	41.75
	65%	8 1/4	40	27 1/2	2.0	57.75	44.5	41.75
	65%	8 1/4	40	28	2.5	57.75	44.5	41.75
	65%	8 3/8	39 3/4	28 1/2	3.0	59.25	45	42
	65%	8 3/8	39 3/4	29	3.5	59.25	45	42
	65%	8 3/8	39 3/4	29 1/2	4.0	59.25	45	42
	65%	8 1/2	39 3/4	30	4.5	61	45	41.75
	65%	8 1/2	39 3/4	30 1/2	5.0	61	45	41.75
	65%	8 1/2	39 3/4	31	5.5	61	45	41.75
	65%	8 1/2	39 7/8	31 1/2	6.0	62.5	44.75	41.75
	65%	8 1/2	39 7/8	32	6.5	62.5	44.75	41.75
	65%	8 1/2	39 7/8	32 1/2	7.0	62.5	44.75	41.75
	65%	8 5/8	39 3/4	33	7.5	64	45.5	41.5
	65%	8 5/8	39 3/4	33 1/2	8.0	64	45.5	41.5

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	8 5/8	39 7/8	25 1/2	0.0	56.5	44	41
	65%	8 5/8	39 7/8	26	0.5	56.5	44	41
	65%	8 5/8	39 7/8	26 1/2	1.0	56.5	44	41
	65%	8 5/8	39 7/8	27	1.5	56.5	44	41
	65%	8 5/8	39 7/8	27 1/2	2.0	56.5	44	41
	65%	8 5/8	39 7/8	28	2.5	56.5	44.25	41
	65%	8 5/8	39 7/8	28 1/2	3.0	56.5	44.25	41
	65%	8 3/4	40	29	3.5	60	45.25	41.25
	65%	8 3/4	40	29 1/2	4.0	60	45.25	41.25
	65%	8 3/4	40	30	4.5	60	45.25	41.25
	65%	8 3/4	40	30 1/2	5.0	60	45.25	41.25
	65%	8 3/4	40	31	5.5	60	45.25	41.25
	65%	8 3/4	40	31 1/2	6.0	60	45.25	41.25
	65%	8 7/8	40 1/4	32	6.5	64.5	46.75	42
	65%	8 7/8	40 1/4	32 1/2	7.0	64.5	46.75	42
	65%	8 7/8	40 1/4	33	7.5	64.5	46.75	42
	65%	8 7/8	40 1/4	33 1/2	8.0	64.5	46.75	42