

Model(s) **Katera XL**  
 Model Year **2008**  
 Limbs **XT500**  
 Cable Guard Bar **8**  
 stealth shot bar **6**  
 Limb Bolt Length **2 1/2**  
 Pocket **31 & 32**

Date **11/26/2007**

Revision

	%	Brace	Axle to	Draw	Base		control	buss
	Letoff	Height	Axle	Length	Cam	String	cable	cable
Z3 Cam	65/75	7	35	25	0.5	50.75	40.25	37.25
	65/75	7	35	25 1/2	1.0	50.75	40.25	37.25
	65/75	7	35	26	1.5	50.75	40.25	37.25
	65/75	7	35	26 1/2	2.0	52.75	40.25	37.25
	65/75	7 1/8	35	27	2.5	52.75	40.25	37.25
	65/75	7	35	27 1/2	3.0	52.75	40.25	37.25
	65/75	7	35 5/8	28	3.5	55.25	41	38
	65/75	7	35 3/4	28 1/2	4.0	55.25	41	38
	65/75	7	35 3/4	29	4.5	55.25	41	38
	65/75	7	36 1/4	29 1/2	5.0	58.25	41.75	38.75
	65/75	7	36 1/4	30	5.5	58.25	41.75	38.75
	65/75	7	36 1/4	30 1/2	6.0	58.25	41.75	38.75
	65/75	7 1/8	36 5/8	31	6.5	60.50	42.25	39.25
	65/75	7	36 1/2	31 1/2	7.0	60.50	42.25	39.25

	%	Brace	Axle to	Draw	Base	Module		control	Buss
	Letoff	Height	Axle	Length	Cam	Position	String	Cable	Cable
Cam & 1/2 Plus	65/75	7 1/4	34 3/4	25	# 1	D	51.50	38.75	36.50
	65/75	7 1/4	34 3/4	26	# 2	D	53.25	38.75	36.50
	65/75	7 1/4	35	27	# 3	D	55	39.25	37
	65/75	7 3/8	35 1/2	28	# 4	D	57	39.75	37.25
	65/75	7 1/2	35 3/4	29	# 5	D	58.50	40	37.50
	65/75	7 5/8	35 3/4	30	# 6	D	60.50	40	37.50
	65/75	7 3/4	36	31	# 7	D	62.25	40.50	37.75