

**Model(s)** HyperTec XT 2000 Hunting and Target  
**Model Year** 2002  
**Limbs** XT 2000 (14")  
**Cable Guard Bar** 8.00  
**Limb Bolt Length** 2.5  
**Pocket** 22/23

**Date** 8/16/2002

**Revision** A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	IYBC
	60 / 75%	5 5/8	33 1/4	23	1	1	85.0	37.0
	60 / 75%	5 5/8	33 1/4	23.5	1.5	1	85.0	37.0
	60 / 75%	5 5/8	33 1/4	24	2	1	85.0	37.0
	60 / 75%	5 5/8	33 1/4	24.5	2.5	1	85.0	37.0
Redline	60 / 75%	5 5/8	33 1/4	25	3	1	85.0	37.0
RC	60 / 75%	5 5/8	33 1/4	25.5	3.5	1	85.0	37.0
2HY2H/T	60 / 75%	5 5/8	33 1/4	26	4	1	85.0	37.0
	60 / 75%	5 5/8	33 1/4	26.5	4.5	1	85.0	37.0
	60 / 75%	5 7/8	33 1/4	27	5	2	88.0	37.5
	60 / 75%	5 7/8	33 1/4	27.5	5.5	2	88.0	37.5
	60 / 75%	5 7/8	33 1/4	28	6	2	88.0	37.5
	60 / 75%	5 7/8	33 1/4	28.5	6.5	2	88.0	37.5
	60 / 75%	5 7/8	33 1/4	29	7	2	88.0	37.5
	60 / 75%	5 3/4	33 1/8	29.5	7.5	2	89.0	38.0
	60 / 75%	5 3/4	33 1/8	30	8	2	89.0	38.0

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*