

Model(s) UltraTec LX Pro Hunting and Target Custom
Model Year 2001
Limbs LX Pro (18")
Cable Guard Bar 10.5
Limb Bolt Length 2.5
Pocket 22/23

Date 11/20/2001

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		65%	7 1/4	46	24	1	B	58.5
AccuWheel	65%	7 1/4	46	25	1	D	58.5	48.0
AW	65%	7 1/4	46	26	1	F	58.5	48.0
2UTLH/T	65%	7 1/4	46 3/8	27	2	C	60.5	48.0
	65%	7 1/4	46 3/8	28	2	F	60.5	48.0
	65%	7 3/8	46 3/8	29	3	B	64.5	48.5
	65%	7 3/8	46 3/8	30	3	D	64.5	48.5
	65%	7 3/8	46 3/8	31	3	F	64.5	48.5
	65%	7 3/8	46 3/8	32	3	H	64.5	48.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		60 / 75%	7 5/8	46 1/4	24	1	A	59.0
	60 / 75%	7 5/8	46 1/4	25	1	C	59.0	47.0
Command	60 / 75%	7 5/8	46 1/4	26	1	E	59.0	47.0
CL/CH	60 / 75%	7 7/8	46	27	2	B	61.0	47.0
2UTLH/T	60 / 75%	7 7/8	46	28	2	D	61.0	47.0
	60 / 75%	7 7/8	46	29	2	F	61.0	47.0
	60 / 75%	7 7/8	46	30	2	H	61.0	47.0
	60 / 75%	7 3/4	46 5/8	31	3	C	65.5	47.5
	60 / 75%	7 3/4	46 5/8	32	3	E	65.5	47.5
	60 / 75%	7 3/4	46 5/8	33	3	G	65.5	47.5

Letoff, brace height, axle to axle length given as a general production guide only