

Model(s) **ProElite**
 Model Year **2006**
 Limbs **XT2000**
 Cable Guard Bar **9 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **31 & 32**

Date **12/8/2005**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	7 3/4	37 7/8	26	D	C&1/2 #1	51	41.5	39.25
	65/75	8	37 3/4	27	D	C&1/2 #2	52	41.5	39.25
cam & 1/2 adjustable	65/75	8 1/8	37 3/4	28	D	C&1/2 #3	52.75	42	39.25
	65/75	8 1/8	37 3/8	29	D	C&1/2 #4	54	42.5	39.75
	65/75	8 1/8	37 5/8	30	D	C&1/2 #5	55.5	42.5	39.75
	65/75	8 1/4	37 13/16	31	D	C&1/2 #6	57	43	40
	65/75	8 3/8	37 7/8	32	D	C&1/2 #7	58.25	43	40

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	7 5/8	37 1/4	25 1/2	1.0	55.25	41.75	39.25
	65%	7 5/8	37 1/4	26	1.5	55.25	41.75	39.25
	65%	7 5/8	37 1/4	26 1/2	2.0	55.25	41.75	39.25
	65%	7 5/8	37 1/4	27	2.5	55.25	41.75	39.25
	65%	7 5/8	37 1/4	27 1/2	3.0	57	42.25	39.25
	65%	7 5/8	37 1/4	28	3.5	57	42.25	39.25
cam & 1/2 spiral	65%	7 5/8	37 1/4	28 1/2	4.0	57	42.25	39.25
	65%	7 5/8	37 3/8	29	4.5	59	42.25	39
	65%	7 5/8	37 3/8	29 1/2	5.0	59	42.25	39
	65%	7 5/8	37 3/8	30	5.5	59	42.25	39
	65%	7 5/8	37 5/8	30 1/2	6.0	60.5	42.25	39.25
	65%	7 5/8	37 5/8	31	6.5	60.5	42.25	39.25
	65%	7 5/8	37 5/8	31 1/2	7.0	60.5	42.25	39.25
	65%	7 5/8	37 5/8	32	7.5	62.25	43.25	39.25
	65%	7 5/8	37 5/8	32 1/2	8.0	62.25	43.25	39.25