

Model(s) Striker II Carbonite Target - JP
 Model Year 1999
 Limbs 4 Piece Laminated Carbon (16")
 Cable Guard Bar ProSet II Med
 Limb Bolt Length 2.5

Date 15-Jan-99

Revision

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
65%	7 1/16	38 3/8	22	1	B	50.75	40.25
65%	7 1/16	38 3/8	23	1	D	50.75	40.25
65%	7 1/16	38 3/16	24	2	B	52.25	40.25
65%	7 3/16	38 3/16	25	2	D	52.25	40.25
65%	7 3/16	38 3/16	26	2	F	52.25	40.25
65%	7 3/16	38 5/8	27	3	A	56.75	40.25
65%	7 3/16	38 5/8	28	3	C	56.75	40.25
65%	7 3/16	38 5/8	29	3	E	56.75	40.25
65%	7 3/16	38 5/8	30	3	H	56.75	40.25

Letoff, brace height, axle to axle length given as a general production guide only

Desc: TUNE/DEFLECTION CHART - STRIKER II CARBONITE TARGET
 File: S2 - TUNE: S2 CARBONITE DATE: 15-Jan-99
 HOYT USA