

Model(s) Havoc XT 2000 Hunting
 Model Year 2001
 Limbs XT 2000 (15" Magnum)
 Cable Guard Bar
 Limb Bolt Length 2.5
 Pocket

Date 7/13/2017

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
		65%	7 1/8	33 1/4	22	1	C	45.75
	65%	7 1/8	33 1/4	23	1	E	45.75	35.25
Command	65%	7 1/8	33 1/4	24	1	G	45.75	35.25
C/D	75 / 65%	7 1/8	33 5/8	25	2	C	48.25	35.25
H25HC/D	75 / 65%	7 1/8	33 5/8	26	2	F	48.25	35.25
	75 / 65%	7 1/8	33 5/8	27	2	H	48.25	35.25
	75 / 65%	7 3/8	33 3/8	28	3	D	51.75	35.75
	75 / 65%	7 3/8	33 3/8	29	3	G	51.75	35.75
	75 / 65%	7 1/4	33 3/4	30	4	E	54.25	36.25
	75 / 65%	7 1/4	33 3/4	31	4	G	54.25	36.25

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
		60 / 75%	7 7/8	33 1/2	25	1	3	87.25
				25.5	1.5	3	87.25	35.25
	60 / 75%	7 7/8	33 1/2	26	2	3	87.25	35.25
				26.5	2.5	3	87.25	35.25
	60 / 75%	7 7/8	33 1/2	27	3	3	87.25	35.25
Saber				27.5	3.5	3	87.25	35.25
B	60 / 75%	8 1/4	33 3/4	28	4	4	89.75	35.75
H25HB				28.5	4.5	4	89.75	35.75
	60 / 75%	8 1/4	33 3/4	29	5	4	89.75	35.75
				29.5	5.5	4	89.75	35.75
	60 / 75%	8 1/4	33 3/4	30	6	4	89.75	35.75
				30.5	6.5	4	89.75	35.75
	60 / 75%	8 1/8	33 7/8	31	7	5	92.75	36.25
				31.5	7.5	5	92.75	36.25
	60 / 75%	8 1/8	33 7/8	32	8	5	92.75	36.25

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	Idler Wheel	String	Buss Cable
		60 / 75%	7 1/2	33 1/8	25	1	A-4	1	83.25
Versa	60 / 75%	7 1/2	33 1/8	26	1	E-5	1	83.25	35.75
V	60 / 75%	7 1/2	33 1/8	27	1	G	1	83.25	35.75
H25HV	60 / 75%	7 5/8	33 1/2	28	2	B-5	2	87.25	36.25
	60 / 75%	7 5/8	33 1/2	29	2	E-7	2	87.25	36.25
	60 / 75%	7 1/2	33 7/8	30	3	B-4	2	91.25	36.75
	60 / 75%	7 1/2	33 7/8	31	3	E-7	2	91.25	36.75
	60 / 75%	7 1/2	33 7/8	32	3	G-9	2	91.25	36.75