

Model(s) HyperTec XT 2000 Target
 Model Year 2001
 Limbs XT 2000
 Cable Guard Bar
 Limb Bolt Length 2.25
 Pocket

Date 1/10/2001
 Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	6	36	24	1.5	3	92.5	38.0
				24.5	2	3	92.5	38.0
	60 / 75%	6	36	25	2.5	3	92.5	38.0
				25.5	3	3	92.5	38.0
Saber B	60 / 75%	6	36	26	3.5	3	92.5	38.0
				26.5	4	4	95.0	38.5
HT5TB	60 / 75%	6 1/4	36 1/4	27	4.5	4	95.0	38.5
				27.5	5	4	95.0	38.5
	60 / 75%	6 1/4	36 1/4	28	5.5	4	95.0	38.5
				28.5	6	4	95.0	38.5
	60 / 75%	6 1/4	36 1/4	29	6.5	4	95.0	38.5
				29.5	7	5	98.0	39.0
	60 / 75%	6 1/5	36 1/2	30	7.5	5	98.0	39.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	5 1/2	35 3/8	20	1	A	48.0	37.5
	65%	5 1/2	35 3/8	21	1	C	48.0	37.5
Command C/D	65%	5 1/2	35 3/8	22	1	E	48.0	37.5
	65 / 75%	5 3/8	35 7/8	23	2	C	51.0	38.0
HT5TC/D	65 / 75%	5 3/8	35 7/8	24	2	E	51.0	38.0
	65 / 75%	5 3/8	35 7/8	25	2	F	51.0	38.0
	65 / 75%	5 1/2	35 7/8	26	3	B	54.5	38.5
	65 / 75%	5 1/2	35 7/8	27	3	D	54.5	38.5
	65 / 75%	5 1/2	35 7/8	28	3	F	54.5	38.5
	65 / 75%	5 3/8	36 1/2	29	4	E	57.5	39.0
	65 / 75%	5 3/8	36 1/2	30	4	G	57.5	39.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Buss Cable
	65%	5 5/8	35	24	1.5	48.5	37.0
	65%	5 5/8	35	24.5	2	48.5	37.0
	65%	5 5/8	35 1/4	25	2.5	50.0	37.0
	65%	5 5/8	35 1/4	25.5	3	50.0	37.0
Master X	65%	5 5/8	35 3/8	26	3.5	51.0	37.5
	65%	5 5/8	35 3/8	26.5	4	51.0	37.5
HT5TX	65%	5 1/2	36 1/8	27	4.5	53.0	38.0
	65%	5 1/2	36 1/8	27.5	5	53.0	38.0
	65%	5 1/2	36 1/8	28	5.5	54.5	38.0
	65%	5 1/2	36 1/8	28.5	6	54.5	38.0
	65%	5 5/8	36 1/8	29	6.5	56.0	38.0
	65%	5 5/8	36 1/8	29.5	7	56.0	38.0
	65%	5 1/2	36 3/8	30	7.5	57.5	38.5
	65%	5 1/2	36 3/8	30.5	8	57.5	38.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	5 3/4	35 3/4	23.5	1	1	89.5	39.5
	60 / 75%	5 3/4	35 3/4	24	1.5	1	89.5	39.5
	60 / 75%	5 3/4	35 3/4	24.5	2	1	89.5	39.5
	60 / 75%	5 3/4	35 3/4	25	2.5	1	89.5	39.5
Redline Z	60 / 75%	5 3/4	35 3/4	25.5	3	1	89.5	39.5
	60 / 75%	5 3/4	35 3/4	26	3.5	1	89.5	39.5
HT5TZ	60 / 75%	5 3/4	35 3/4	26.5	4	1	89.5	39.5
	60 / 75%	5 3/4	35 3/4	27	4.5	1	89.5	39.5
	60 / 75%	5 3/4	35 7/8	27.5	5	2	92.5	40.0
	60 / 75%	5 3/4	35 7/8	28	5.5	2	92.5	40.0
	60 / 75%	5 3/4	35 7/8	28.5	6	2	92.5	40.0
	60 / 75%	5 3/4	35 7/8	29	6.5	2	92.5	40.0
	60 / 75%	5 3/4	35 7/8	29.5	7	2	92.5	40.0
	60 / 75%	5 3/4	35 3/4	30	7.5	2	93.5	40.5
	60 / 75%	5 3/4	35 3/4	30.5	8	2	93.5	40.5