

Model(s) HavocTec XT 2000 Hunting and Target
 Model Year 2002
 Limbs XT 2000 (14")
 Cable Guard Bar 9.00
 Limb Bolt Length 2.5
 Pocket 22 Htg / 23 Tgt

Date 3/4/2002
 Revision B

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65%	6 3/4	31 1/4	21	1	A	44.0	33.0
	65%	6 3/4	31 1/4	22	1	D	44.0	33.0
AccuWheel	65%	6 3/4	31 1/4	23	1	F	44.0	33.0
AW	65%	6 3/4	31 1/2	24	2	C	46.0	33.0
2HT2H/T	65%	6 3/4	31 1/2	25	2	G	46.0	33.0
	65%	6 5/8	32 1/8	26	3	C	50.5	34.0
	65%	6 5/8	32 1/8	27	3	F	50.5	34.0
	65%	6 5/8	32 1/8	28	3	H	50.5	34.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65 / 75%	6 7/8	31 3/4	21	1	B	44.5	32.5
	65 / 75%	6 7/8	31 3/4	22	1	D	44.5	32.5
	65 / 75%	6 7/8	31 3/4	23	1	F	44.5	32.5
Command	65 / 75%	6 7/8	32	24	2	C	48.0	33.0
CL/CH	65 / 75%	6 7/8	32	25	2	F	48.0	33.0
2HT2H/T	65 / 75%	6 7/8	32	26	2	H	48.0	33.0
	65 / 75%	7 1/8	32 3/8	27	3	B	51.5	33.0
	65 / 75%	7 1/8	32 3/8	28	3	D	51.5	33.0
	65 / 75%	7 1/8	32 3/8	29	3	G	51.5	33.0
	65 / 75%	7 1/2	32 3/8	30	4	F	54.0	33.0
	65 / 75%	7 1/2	32 3/8	31	4	H	54.0	33.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	DT String	CBC	IYBC	
	60 / 75%	7 5/8	31 1/4	24	1	3	51.0	38.0	33.0	
	60 / 75%	7 5/8	31 1/4	24.5	1.5	3	51.0	38.0	33.0	
	60 / 75%	7 5/8	31 1/4	25	2	3	51.0	38.0	33.0	
	60 / 75%	7 5/8	31 1/4	25.5	2.5	3	51.0	38.0	33.0	
	60 / 75%	7 5/8	31 1/4	26	3	3	51.0	38.0	33.0	
	60 / 75%	7 5/8	31 1/4	26.5	3.5	3	51.0	38.0	33.0	
	Excel	60 / 75%	7 1/2	31 1/4	27	4.5	4	53.0	38.5	33.5
	EC	60 / 75%	7 1/2	31 1/4	27.5	5	4	53.0	38.5	33.5
	2HT2H/T	60 / 75%	7 1/2	31 1/4	28	5.5	4	53.0	38.5	33.5
		60 / 75%	7 1/2	31 1/4	28.5	6	4	53.0	38.5	33.5
	60 / 75%	7 3/4	31 1/2	29	6.5	5	55.5	40.0	34.0	
	60 / 75%	7 3/4	31 1/2	29.5	7	5	55.5	40.0	34.0	
	60 / 75%	7 3/4	31 1/2	30	7.5	5	55.5	40.0	34.0	
	60 / 75%	7 3/4	31 1/2	30.5	8	5	55.5	40.0	34.0	

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
	60 / 75%	7 1/4	32	24	1	A-1	3	51.5	38.0	35.0
	60 / 75%	7 1/4	32	25	1	E-5	3	51.5	38.0	35.0
Versa	60 / 75%	7 1/4	32	26	1	G-7	3	51.5	38.0	35.0
VC	60 / 75%	7 1/4	32	26	1	G-7	3	51.5	38.0	35.0
2HT2H/T	60 / 75%	7 3/8	31 7/8	27	2	D-4	4	53.5	39.0	35.0
	60 / 75%	7 3/8	31 7/8	28	2	F-6	4	53.5	39.0	35.0
	60 / 75%	7 1/2	32 3/8	29	3	D-4	5	57.0	40.0	36.0
	60 / 75%	7 1/2	32 3/8	30	3	F-6	5	57.0	40.0	36.0
	60 / 75%	7 1/2	32 3/8	31	3	H-8	5	57.0	40.0	36.0

Letoff, brace height, axle to axle length given as a general production guide only