

Model(s) **PROTEC**
Model Year **2003**
Limbs **XT3000**
Cable Guard Bar **10.50**
Limb Bolt Length **2.50**
Pocket **#22 or #23**

Date 3/19/2003

Revision **H**

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	CAM & MODULE	MODULE POSITION	STRING	HCBC
AccuWheel	65%	8 1/8	40 5/8	23	1	A	53	42.5
	65%	8 1/8	40 5/8	24	1	C	53	42.5
	65%	8 1/8	40 5/8	25	1	F	53	42.5
AW	65%	8 1/4	40 7/8	26	2	B	55	42.5
	65%	8 1/4	40 7/8	27	2	D	55	42.5
	65%	8 1/4	40 7/8	28	2	G	55	42.5
	65%	8 1/8	41 1/8	29	3	C	59	43
	65%	8 1/8	41 1/8	30	3	E	59	43
	65%	8 1/8	41 1/8	31	3	G	59	43

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	CAM & MODULE	MODULE POSITION	STRING	HCBC	HYBC
Cam & 1/2 Adjustable	65/75%	8 3/4	40 1/4	27	A-1	C	53.5	44.25	42.0
	65/75%	8 7/8	40 5/8	28	B-2	C	54.5	44.75	42.5
	65/75%	8 7/8	41 1/8	29	C-3	C	55.5	45.0	42.5
	65/75%	8 7/8	41	30	D-4	C	57.5	45.75	43
	65/75%	9	41	31	E-5	C	58.5	45.75	43.0
	65/75%	9	41 1/4	32	F-6	C	60.0	46.5	43.5
	65/75%	9	41 1/4	33	G-7	C	61.5	47.25	43.75

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE
Spiral Cam & 1/2	65%	8 3/8	40 3/4	27.5	1	59.0	45.5	42.75
	65%	8 3/8	40 3/4	28	1.5	59.0	45.5	42.75
	65%	8 3/8	40 3/4	28.5	2	59.0	45.5	42.75
	65%	8 3/8	40 3/4	29	2.5	59.0	45.5	42.75
	65%	8 5/8	40 3/8	29.5	3	60.5	45.5	42.5
	65%	8 5/8	40 3/8	30	3.5	60.5	45.5	42.5
	65%	8 5/8	40 3/8	30.5	4	60.5	45.5	42.5
	65%	9	39 3/4	31	4.5	61.5	45.0	42.0
	65%	9	39 3/4	31.5	5	61.5	45.0	42.0
	65%	9	39 3/4	32	5.5	61.5	45.0	42.0
	65%	8 5/8	40 1/2	32.5	6	63.5	45.25	42.25
	65%	8 5/8	40 1/2	33	6.5	63.5	45.25	42.25
	65%	8 5/8	40 1/2	33.5	7	63.5	45.25	42.25
	65%	8 5/8	40 5/8	34	7.5	65.5	46.25	42.25
	65%	8 5/8	40 5/8	34.5	8	65.5	46.25	42.25