

Vantage Elite Plus - XT2000 - Spiral Cam & 1/2

| CAM | LETOFF | BRACE HEIGHT | AXLE TO AXLE | DRAW LENGTH | MODULE POSITION | BASE CAM | STRING | CONTROL CABLE | BUSS CABLE | CAM FAMILY | 40 | 50 | 60 | 70 |
|------------------|--------|--------------|--------------|-------------|-----------------|----------|--------|---------------|------------|------------|----|----|----|-----|
| | | | | | | | | | | | 40 | 50 | 60 | 70 |
| Spiral Cam & 1/2 | 65% | 7 3/4 | 39 3/8 | 25 | N/A | 0.5 | 57.25 | 44.00 | 41.25 | Size 1 | 58 | 70 | 86 | 98 |
| | 65% | 7 3/4 | 39 3/8 | 25 1/2 | N/A | 1 | 57.25 | 44.00 | 41.25 | | 58 | 70 | 86 | 98 |
| | 65% | 7 3/4 | 39 3/8 | 26 | N/A | 1.5 | 57.25 | 44.00 | 41.25 | | 58 | 72 | 86 | 100 |
| | 65% | 7 3/4 | 39 3/8 | 26 1/2 | N/A | 2 | 57.25 | 44.00 | 41.25 | | 58 | 72 | 88 | 100 |
| | 65% | 7 3/4 | 39 3/8 | 27 | N/A | 2.5 | 57.25 | 44.00 | 41.25 | | 58 | 72 | 88 | 100 |
| | 65% | 7 3/4 | 39 7/8 | 27 1/2 | N/A | 3 | 59.50 | 45.00 | 42.00 | Size 2 | 58 | 72 | 86 | 100 |
| | 65% | 7 3/4 | 39 7/8 | 28 | N/A | 3.5 | 59.50 | 45.00 | 42.00 | | 58 | 72 | 86 | 100 |
| | 65% | 7 3/4 | 39 3/4 | 28 1/2 | N/A | 4 | 59.50 | 45.00 | 42.00 | | 58 | 72 | 86 | 100 |
| | 65% | 7 3/4 | 40 3/8 | 29 | N/A | 4.5 | 61.75 | 45.25 | 42.00 | Size 3 | 58 | 70 | 82 | 98 |
| | 65% | 7 3/4 | 40 3/8 | 29 1/2 | N/A | 5 | 61.75 | 45.25 | 42.00 | | 58 | 70 | 82 | 98 |
| | 65% | 7 3/4 | 40 3/8 | 30 | N/A | 5.5 | 61.75 | 45.25 | 42.00 | | 58 | 70 | 82 | 98 |
| | 65% | 7 3/4 | 40 3/4 | 30 1/2 | N/A | 6 | 63.50 | 45.50 | 42.50 | Size 4 | 58 | 70 | 82 | 98 |
| | 65% | 7 3/4 | 40 3/4 | 31 | N/A | 6.5 | 63.50 | 45.50 | 42.50 | | 58 | 70 | 82 | 98 |
| | 65% | 7 3/4 | 40 3/4 | 31 1/2 | N/A | 7 | 63.50 | 45.50 | 42.50 | | 58 | 70 | 82 | 98 |
| | 65% | 7 1/2 | 40 7/8 | 32 | N/A | 7.5 | 65.25 | 46.50 | 42.50 | Size 5 | 56 | 68 | 82 | 94 |
| | 65% | 7 1/2 | 40 7/8 | 32 1/2 | N/A | 8 | 65.25 | 46.50 | 42.50 | | 56 | 68 | 82 | 94 |

* = Shipped module position

Vantage Elite Plus - XT2000 - GTX Cam & 1/2

| CAM | LETOFF | BRACE HEIGHT | AXLE TO AXLE | DRAW LENGTH | MODULE POSITION | BASE CAM | STRING | CONTROL CABLE | BUSS CABLE | CAM FAMILY | 40 | 50 | 60 | 70 |
|---------|---------|--------------|--------------|-------------|-----------------|----------|--------|---------------|------------|------------|----|----|----|----|
| | | | | | | | | | | | 40 | 50 | 60 | 70 |
| GTX Cam | 65/75 % | 7 7/8 | 40 | 25 | B | #1 | 52.75 | 43.75 | 41.50 | N/A | 54 | 68 | 80 | 92 |
| | 65/75 % | 7 7/8 | 40 | 25 1/2 | C | #1 | 52.75 | 43.75 | 41.50 | N/A | 54 | 68 | 80 | 92 |
| | 65/75 % | 7 7/8 | 40 | 26 | D* | #1 | 52.75 | 43.75 | 41.50 | N/A | 54 | 68 | 80 | 92 |
| | 65/75 % | 7 7/8 | 40 | 26 1/2 | E | #1 | 52.75 | 43.75 | 41.50 | N/A | 54 | 68 | 80 | 92 |
| | 65/75 % | 7 7/8 | 40 1/8 | 26 | B | #2 | 53.75 | 44.00 | 41.75 | N/A | 52 | 66 | 78 | 90 |
| | 65/75 % | 7 7/8 | 40 1/8 | 26 1/2 | C | #2 | 53.75 | 44.00 | 41.75 | N/A | 52 | 66 | 78 | 90 |
| | 65/75 % | 7 7/8 | 40 1/8 | 27 | D* | #2 | 53.75 | 44.00 | 41.75 | N/A | 52 | 66 | 78 | 90 |
| | 65/75 % | 7 7/8 | 40 1/8 | 27 1/2 | E | #2 | 53.75 | 44.00 | 41.75 | N/A | 52 | 66 | 78 | 90 |
| | 65/75 % | 8 | 40 1/4 | 27 | B | #3 | 55.25 | 44.25 | 42.00 | N/A | 50 | 64 | 76 | 86 |
| | 65/75 % | 8 | 40 1/4 | 27 1/2 | C | #3 | 55.25 | 44.25 | 42.00 | N/A | 50 | 64 | 76 | 86 |
| | 65/75 % | 8 | 40 1/4 | 28 | D* | #3 | 55.25 | 44.25 | 42.00 | N/A | 50 | 64 | 76 | 86 |
| | 65/75 % | 8 | 40 1/4 | 28 1/2 | E | #3 | 55.25 | 44.25 | 42.00 | N/A | 50 | 64 | 76 | 86 |
| | 65/75 % | 8 | 40 3/8 | 28 | B | #4 | 56.75 | 44.50 | 42.25 | N/A | 48 | 64 | 74 | 84 |
| | 65/75 % | 8 | 40 3/8 | 28 1/2 | C | #4 | 56.75 | 44.50 | 42.25 | N/A | 48 | 64 | 74 | 84 |
| | 65/75 % | 8 | 40 3/8 | 29 | D* | #4 | 56.75 | 44.50 | 42.25 | N/A | 48 | 64 | 74 | 84 |
| | 65/75 % | 8 | 40 3/8 | 29 1/2 | E | #4 | 56.75 | 44.50 | 42.25 | N/A | 48 | 64 | 74 | 84 |
| | 65/75 % | 8 1/8 | 40 1/2 | 29 | B | #5 | 58.50 | 44.75 | 42.50 | N/A | 46 | 58 | 70 | 80 |
| | 65/75 % | 8 1/8 | 40 1/2 | 29 1/2 | C | #5 | 58.50 | 44.75 | 42.50 | N/A | 46 | 58 | 70 | 80 |
| | 65/75 % | 8 1/8 | 40 1/2 | 30 | D* | #5 | 58.50 | 44.75 | 42.50 | N/A | 46 | 58 | 70 | 80 |
| | 65/75 % | 8 1/8 | 40 1/2 | 30 1/2 | E | #5 | 58.50 | 44.75 | 42.50 | N/A | 46 | 58 | 70 | 80 |
| | 65/75 % | 8 | 41 | 30 | B | #6 | 59.75 | 45.25 | 43.25 | N/A | 48 | 60 | 72 | 82 |
| | 65/75 % | 8 | 41 | 30 1/2 | C | #6 | 59.75 | 45.25 | 43.25 | N/A | 48 | 60 | 72 | 82 |
| | 65/75 % | 8 | 41 | 31 | D* | #6 | 59.75 | 45.25 | 43.25 | N/A | 48 | 60 | 72 | 82 |
| | 65/75 % | 8 | 41 | 31 1/2 | E | #6 | 59.75 | 45.25 | 43.25 | N/A | 48 | 60 | 72 | 82 |

Model: Vantage Elite Plus
Model Year: 2012

Limb: XT2000
Cable Guard: 9.00

Adjustable Shot Bar: N/A
Limb Bolt Length: 2.5

Pocket: #35 & 38
Rocker: #6

Date: 10/14/11
Revision: