

## Pro Comp Elite - XT2000 - Spiral X Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE	CAM FAMILY
Spiral X Cam	65%	7 5/8	36 3/4	24 1/2	N/A	0.5	54.50	41.38	38.75	Size 1
	65%	7 5/8	36 3/4	25	N/A	1	54.50	41.38	38.75	
	65%	7 5/8	36 3/4	25 1/2	N/A	1.5	54.50	41.38	38.75	
	65%	7 5/8	36 7/8	26	N/A	2	54.50	41.38	38.75	
	65%	7 5/8	36 7/8	26 1/2	N/A	2.5	54.50	41.38	38.75	
	65%	7 5/8	37	27	N/A	3	56.75	42.25	39.25	Size 2
	65%	7 5/8	37	27 1/2	N/A	3.5	56.75	42.25	39.25	
	65%	7 5/8	37	28	N/A	4	56.75	42.25	39.25	
	65%	7 5/8	37 1/8	28 1/2	N/A	4.5	58.50	42.25	39.00	Size 3
	65%	7 5/8	37 1/8	29	N/A	5	58.50	42.25	39.00	
	65%	7 5/8	37 1/8	29 1/2	N/A	5.5	58.50	42.25	39.00	
	65%	7 5/8	37 5/8	30	N/A	6	60.50	42.50	39.50	Size 4
	65%	7 5/8	37 5/8	30 1/2	N/A	6.5	60.50	42.50	39.50	
	65%	7 5/8	37 5/8	31	N/A	7	60.50	42.50	39.50	
	65%	7 5/8	38	31 1/2	N/A	7.5	62.50	43.75	39.63	Size 5
	65%	7 5/8	38	32	N/A	8	62.50	43.75	39.63	

\* = Shipped module position

## Pro Comp Elite - XT2000 - GTX Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE	CAM FAMILY
65/75 %	7 3/4	37	24 1/2	B	#1	49.50	40.50	38.50	N/A	
65/75 %	7 3/4	37	25	C	#1	49.50	40.50	38.50	N/A	
65/75 %	7 3/4	37	25 1/2	D	#1	49.50	40.50	38.50	N/A	
<b>65/75 %</b>	<b>7 3/4</b>	<b>37</b>	<b>26</b>	<b>E*</b>	<b>#1</b>	<b>49.50</b>	<b>40.50</b>	<b>38.50</b>	<b>N/A</b>	
65/75 %	7 15/16	36 15/16	25 1/2	B	#2	50.50	40.75	38.75	N/A	
65/75 %	7 15/16	36 15/16	26	C	#2	50.50	40.75	38.75	N/A	
65/75 %	7 15/16	36 15/16	26 1/2	D	#2	50.50	40.75	38.75	N/A	
65/75 %	<b>7 15/16</b>	<b>36 15/16</b>	<b>27</b>	<b>E*</b>	<b>#2</b>	<b>50.50</b>	<b>40.75</b>	<b>38.75</b>	<b>N/A</b>	
65/75 %	8	37 3/16	26 1/2	B	#3	52.25	41.00	39.00	N/A	
65/75 %	8	37 3/16	27	C	#3	52.25	41.00	39.00	N/A	
65/75 %	8	37 3/16	27 1/2	D	#3	52.25	41.00	39.00	N/A	
65/75 %	<b>8</b>	<b>37 3/16</b>	<b>28</b>	<b>E*</b>	<b>#3</b>	<b>52.25</b>	<b>41.00</b>	<b>39.00</b>	<b>N/A</b>	
65/75 %	8	37 1/2	27 1/2	B	#4	54.00	41.50	39.50	N/A	
65/75 %	8	37 1/2	28	C	#4	54.00	41.50	39.50	N/A	
65/75 %	8	37 1/2	28 1/2	D	#4	54.00	41.50	39.50	N/A	
65/75 %	<b>8</b>	<b>37 1/2</b>	<b>29</b>	<b>E*</b>	<b>#4</b>	<b>54.00</b>	<b>41.50</b>	<b>39.50</b>	<b>N/A</b>	
65/75 %	8	37 5/8	28 1/2	B	#5	55.75	42.00	39.75	N/A	
65/75 %	8	37 5/8	29	C	#5	55.75	42.00	39.75	N/A	
65/75 %	8	37 5/8	29 1/2	D	#5	55.75	42.00	39.75	N/A	
65/75 %	<b>8</b>	<b>37 5/8</b>	<b>30</b>	<b>E*</b>	<b>#5</b>	<b>55.75</b>	<b>42.00</b>	<b>39.75</b>	<b>N/A</b>	
65/75 %	8	38	29 1/2	B	#6	57.00	42.25	40.25	N/A	
65/75 %	8	38	30	C	#6	57.00	42.25	40.25	N/A	
65/75 %	8	38	30 1/2	D	#6	57.00	42.25	40.25	N/A	
65/75 %	<b>8</b>	<b>38</b>	<b>31</b>	<b>E*</b>	<b>#6</b>	<b>57.00</b>	<b>42.25</b>	<b>40.25</b>	<b>N/A</b>	

Model: Pro Comp Elite

Limb: XT2000

Stealth Shot Bar: N/A

Pocket: W3

Model Year: 2013

Cable Guard: 9.00

Limb Bolt Length: 1.75

Rocker: #6

Air Shox Arm Copy of PE-9999-989 Pro Comp Elite Z tune chart

11/1/12

Engineering Manager