

Model(s) AccuTec Carbonite Target & Hunting
Model Year 1998
Limbs 4 Piece Laminated Carbon (16")
Cable Guard Bar AT Carb. Med.
Limb Bolt Length 2.75
Physical Weight 5 lbs. 1 oz.

Date 6-Jan-98
Revision A

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	8 1/4	40 1/4	24	1	B	52.75	42.25
	65%	8 1/4	40 1/4	25	1	D	52.75	42.25
AW	65%	8 1/4	40 1/4	26	2	B	54.25	42.25
AUNHA	65%	8 1/4	40 1/4	27	2	D	54.25	42.25
AUNTA	65%	8 1/4	40 1/4	28	3	A	57.75	42.25
	65%	8 1/4	40 1/4	29	3	C	57.75	42.25
	65%	8 1/4	40 1/4	30	3	E	57.75	42.25
	65%	8 1/4	40 1/4	31	3	G	57.75	42.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	75%	8 3/8	40 3/8	27	2	B	55.25	42.25
	75%	8 3/8	40 3/8	28	2	D	55.25	42.25
CC	75%	8 3/8	40 3/8	29	2	F	55.25	42.25
AUNHC	75%	8 3/8	40 3/8	30	3	B	58.75	42.75
AUNTC	75%	8 3/8	40 3/8	31	3	D	58.75	42.75
	75%	8 3/8	40 3/8	32	3	F	58.75	42.75
	75%	8 3/8	40 3/8	33	3	H	58.75	42.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	8 3/8	40 3/8	27	2	B	55.25	42.25
	65%	8 3/8	40 3/8	28	2	D	55.25	42.25
CC	65%	8 3/8	40 3/8	29	2	F	55.25	42.25
AUNHD	65%	8 3/8	40 3/8	30	3	B	58.75	42.75
AUNTD	65%	8 3/8	40 3/8	31	3	D	58.75	42.75
	65%	8 3/8	40 3/8	32	3	F	58.75	42.75
	65%	8 3/8	40 3/8	33	3	H	58.75	42.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	8 1/4	40 1/2	27	2	B	56.75	42.25
	65%	8 1/4	40 1/2	28	2	D	56.75	42.25
PC	65%	8 1/4	40 1/2	29	2	F	56.75	42.25
AUNHP	65%	8 1/4	40 1/2	30	3	B	60.75	42.75
AUNTP	65%	8 1/4	40 1/2	31	3	D	60.75	42.75
	65%	8 1/4	40 1/2	32	3	F	60.75	42.75
	65%	8 1/4	40 1/2	33	3	H	60.75	42.75

Letoff, brace height, axle to axle length given as a general production guide only
 THIS DATA SHEET VOID FOR PRODUCTION USE UNLESS RELEASE STAMP APPEARS IN RED

Desc: TUNE/DEFLECTION CHART - AU CARBONITE TARGET & HUNTING
 File: AU - TUNE: AU CARBONITE
 DATE: 6-Jan-98
 HOYT USA