

Model(s) ProTec
Model Year 2004
Limbs XT2000
Cable Guard Bar 9 1/2
Limb Bolt Length 2 1/2
Pocket 27 & 28 Low

Date 1/26/2004

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Can / Module	Module Position	String	HCBC	HYBC
	65 / 75%	7 7/8	38 1/8	26	A-1	D	51.0	42.0	39.75
Cam	65 / 75%	7 7/8	38 1/4	27	B-2	D	52.0	42.25	40.0
&1/2	65 / 75%	8 1/8	38	28	C-3	C	53.0	42.25	39.75
Adjustable	65 / 75%	8 1/8	38 1/8	29	D-4	C	54.5	43.0	40.25
	65 / 75%	8 3/4	38	30	E-5	C	55.5	42.75	40.0
	65 / 75%	8 3/8	38 1/8	31	F-6	C	57.0	43.25	40.25
	65 / 75%	8 1/2	38 1/4	32	G-7	C	58.5	44.0	40.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Control Cable	Buss Cable
Cam / Wheel	65%	8	37	26	1	55.0	41.5	39.0
	65%	8	37	26.5	1.5	55.0	41.5	39.0
	65%	8	37	27	2	55.0	41.5	39.0
Cam	65%	8	37	27.5	2.5	55.0	41.5	39.0
&1/2	65%	8 1/8	36 5/8	28	3	56.5	41.75	38.75
Spiral	65%	8 1/8	36 5/8	28.5	3.5	56.5	41.75	38.75
	65%	8 1/8	36 5/8	29	4	56.5	41.75	38.75
	68%	8 1/4	36 7/8	29.5	4.5	58.5	42	38.75
	68%	8 1/4	36 7/8	30	5	58.5	42	38.75
	68%	8 1/4	36 7/8	30.5	5.5	58.5	42	38.75
	65%	8	37 1/2	31	6	60.5	42.25	39.25
	65%	8	37 1/2	31.5	6.5	60.5	42.25	39.25
	65%	8	37 1/2	32	7	60.5	42.25	39.25
	65%	8 1/4	37	32.5	7.5	61.5	42.5	38.5
	65%	8 1/4	37	33	8	61.5	42.5	38.5