

Model(s) 38 Pro
Model Year 2007
Limbs XT2000
Cable Guard Bar 9 1/2
Stealth shot bar 7 1/4
Limb Bolt Length 2 1/2
Pocket 31 & 32

Date
Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	8 5/16	38 11/16	27 1/8	E	1	51.5	42.5	40.25
	65/75	8 3/8	38 9/16	28 1/16	E	2	52.5	42.5	40.25
	65/75	8 3/8	38 7/8	29 1/6	E	3	53.75	43.25	40.5
	65/75	8 3/8	39	30 3/16	E	4	55.25	43.75	41
	65/75	8 1/2	38 7/8	31 1/16	E	5	56.75	43.75	41
	65/75	8 1/2	39 1/4	32 1/8	E	6	58.25	44.25	41.25
	65/75	8 5/8	39 5/16	33 1/4	E	7	59.5	45	41.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length		Base Cam	String	control Cable	Buss Cable	Cam Size
C2	65%	8 1/4	38 1/16	26		0.5	52	43.25	40	Base Size 1
	65%	8 1/4	38 1/16	26 1/2		1	52	43.25	40	
	65%	8 3/16	38 1/16	27		1.5	52	43.25	40	
	65%	8 3/16	38 1/16	27 1/2		2	52	43.25	40	
	65%	8 1/4	37 7/8	28		2.5	54.25	43	40.5	Base Size 2
	65%	8 1/4	37 7/8	28 1/2		3	54.25	43	40.5	
	65%	8 3/16	38	29		3.5	54.25	43	40.5	
	65%	8 1/8	38 7/16	29 1/2		4	57.25	43.5	41	Base Size 3
	65%	8 3/16	38 5/16	30		4.5	57.25	43.5	41	
	65%	8 1/8	38 1/2	30 1/2		5	57.25	43.5	41	
	65%	8 5/16	38 11/16	31		5.5	60	44	41.25	Base Size 4
	65%	8 5/16	38 3/4	31 1/2		6	60	44	41.25	
	65%	8 5/16	38 3/4	32		6.5	60	44	41.25	