

Model(s) ProTec XT 2000 Hunting and Target
Model Year 2002
Limbs XT 2000 (14")
Cable Guard Bar 9.50
Limb Bolt Length 2.5
Pocket 22/23

Date 12/12/2001

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65 / 75%	7 7/8	37 5/8	23	1	B	50.5	38.5
	65 / 75%	7 7/8	37 5/8	24	1	D	50.5	38.5
	65 / 75%	7 7/8	37 5/8	25	1	F	50.5	38.5
Command	65 / 75%	7 7/8	38	26	2	C	53.5	39.0
CL/CH	65 / 75%	7 7/8	38	27	2	E	53.5	39.0
2PT2H/T	65 / 75%	7 7/8	38	28	2	G	53.5	39.0
	65 / 75%	8 1/8	38 1/8	29	3	C	57.5	39.0
	65 / 75%	8 1/8	38 1/8	30	3	E	57.5	39.0
	65 / 75%	8 1/8	38 1/8	31	3	G	57.5	39.0
	65 / 75%	8 1/4	38 3/8	32	4	F	60.0	39.0
	65 / 75%	8 1/4	38 3/8	33	4	H	60.0	39.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	DT String	CBC	IYBC
	60 / 75%	8 1/2	37 3/4	26	1	3.0	57.5	44.5	39.5
	60 / 75%	8 1/2	37 3/4	26.5	1.5	3.0	57.5	44.5	39.5
	60 / 75%	8 1/2	37 3/4	27	2	3.0	57.5	44.5	39.5
	60 / 75%	8 1/2	37 3/4	27.5	2.5	3.0	57.5	44.5	39.5
Excel	60 / 75%	8 1/2	37 3/4	28	3	3.0	57.5	44.5	39.5
EC	60 / 75%	8 1/2	37 3/4	28.5	3.5	3.0	57.5	44.5	39.5
2PT2H/T	60 / 75%	8 5/8	37 1/8	29	4	4.0	59.0	44.5	39.5
	60 / 75%	8 5/8	37 1/8	29.5	4.5	4.0	59.0	44.5	39.5
	60 / 75%	8 5/8	37 1/8	30	5	4.0	59.0	44.5	39.5
	60 / 75%	8 5/8	37 1/8	30.5	5.5	4.0	59.0	44.5	39.5
	60 / 75%	8 5/8	37 1/8	31	6	4.0	59.0	44.5	39.5
	60 / 75%	8 5/8	38	31.5	6.5	5.0	61.5	46.5	40.5
	60 / 75%	8 5/8	38	32	7	5.0	61.5	46.5	40.5
	60 / 75%	8 5/8	38	32.5	7.5	5.0	61.5	46.5	40.5
	60 / 75%	8 5/8	38	33	8	5.0	61.5	46.5	40.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
	60 / 75%	8 1/4	38 1/4	26	1	A-1	3	57.0	44.5	41.0
Versa	60 / 75%	8 1/4	38 1/4	27	1	E-5	3	57.0	44.5	41.0
VC	60 / 75%	8 1/4	38 1/4	28	1	G-7	3	57.0	44.5	41.0
2PT2H/T	60 / 75%	8 3/8	37 7/8	29	2	D-4	4	59.5	45.0	41.0
	60 / 75%	8 3/8	37 7/8	30	2	F-6	4	59.5	45.0	41.0
	60 / 75%	8 1/2	38 1/4	31	3	B-2	5	63.5	46.5	42.0
	60 / 75%	8 1/2	38 1/4	32	3	D-4	5	63.5	46.5	42.0
	60 / 75%	8 1/2	38 1/4	33	3	F-6	5	63.5	46.5	42.0

Letoff, brace height, axle to axle length given as a general production guide only