

Model(s) ProTec LX Pro Hunting and Target
Model Year 2002
Limbs LX Pro (18")
Cable Guard Bar 11.25
Limb Bolt Length 2.5
Pocket 22/23

Date 6/13/2002
Revision C

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		65%	8 1/2	46 3/4	25	1	B	59.0
	65%	8 1/2	46 3/4	26	1	D	59.0	48.5
Accuwheel	65%	8 1/2	46 3/4	27	1	F	59.0	48.5
AW	65%	8 1/2	46 3/4	28	2	C	61.0	48.5
2PTLH/T	65%	8 1/2	46 3/4	29	2	E	61.0	48.5
	65%	8 1/2	46 3/4	30	2	G	61.0	48.5
	65%	8 1/2	47	31	3	C	65.0	49.0
	65%	8 1/2	47	32	3	E	65.0	49.0
	65%	8 1/2	47	33	3	G	65.0	49.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		65 / 75%	8 7/8	46 5/8	25	1	B	59.5
	65 / 75%	8 7/8	46 5/8	26	1	D	59.5	47.5
Command	65 / 75%	8 7/8	46 5/8	27	1	E	59.5	47.5
CL/CH	65 / 75%	8 7/8	46 5/8	28	1	G	59.5	47.5
2PTLH/T	65 / 75%	9 1/8	46 5/8	29	2	B	61.5	47.5
	65 / 75%	9 1/8	46 5/8	30	2	D	61.5	47.5
	65 / 75%	9 1/8	46 5/8	31	2	G	61.5	47.5
	65 / 75%	9	47	32	3	C	66.0	48.0
	65 / 75%	9	47	33	3	E	66.0	48.0
	65 / 75%	9	47	34	3	H	66.0	48.0

Letoff, brace height, axle to axle length given as a general production guide only