

Model(s) 38 Ultra
Model Year 2007
Limbs XT1000
Cable Guard Bar 9
Stealth shot bar 6 5/8
Limb Bolt Length 2 1/2
Pocket 31 & 32

Date

Revision

	% Lettoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2	65/75	7 3/4	38 1/8	26 1/4	D	1	51.25	41.75	39.5
	65/75	7 13/16	38	27	D	2	52	42	39.5
	65/75	7 3/4	38 1/16	28	D	3	53.25	42.25	39.5
	65/75	7 11/16	38	29	D	4	54.75	42.75	40
	65/75	7 7/8	37 7/8	30	D	5	56	42.75	40
	65/75	7 7/8	38 1/8	31	D	6	57.25	43.25	40.25
	65/75	8 1/16	38 1/8	32	D	7	58.5	43.75	40.25

	% Lettoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable	Cam Size
Vector cam	65%/75%	7 7/16	37 7/8	27	1	55.25	43	40.25	Base Size 1
	65%/75%	7 7/16	37 13/16	27 1/2	1 1/2	55.25	43	40.25	
	65%/75%	7 7/16	37 13/16	28	2	55.25	43	40.25	
	65%/75%	7 7/16	37 7/8	28 1/2	2 1/2	55.25	43	40.25	
	65%/75%	7 7/16	37 3/4	29	3	55.25	43	40.25	
	65%/75%	7 1/2	37 7/8	29 1/2	3 1/2	57.75	43.25	40.5	Base Size 2
	65%/75%	7 1/2	37 7/8	30	4	57.75	43.25	40.5	
	65%/75%	7 1/2	37 7/8	30 1/2	4 1/2	57.75	43.25	40.5	
	65%/75%	7 1/2	38 1/16	31	5	60.25	43.75	40.75	Base Size 3
	65%/75%	7 1/2	38 1/16	31 1/2	5 1/2	60.25	43.75	40.75	
	65%/75%	7 1/2	38 1/16	32	6	60.25	43.75	40.75	
	65%/75%	7 5/8	38	32 1/2	6 1/2	62.25	44.25	40.75	Base Size 4
	65%/75%	7 9/16	38	33	7	62.25	44.25	40.75	