

Model(s) InTec Carbonite Hunting and Target
 Model Year 1999
 Limbs 4 Piece Laminated Carbon (16")
 Cable Guard Bar AT Carb. Short
 Limb Bolt Length 2.5

Date 14-Apr-99

Revision B

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC ITNHC ITNTC	75%	7 1/4	40	26	2	B	55.25	41.75
	75%	7 1/4	40	27	2	D	55.25	41.75
	75%	7 1/4	40	28	2	F	55.25	41.75
	75%	7 1/4	40	29	3	B	58.75	42.25
	75%	7 1/4	40	30	3	D	58.75	42.25
	75%	7 1/4	40	31	3	F	58.75	42.25
	75%	7 3/8	39 5/8	32	4	F	60.25	41.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC ITNHD ITNTD	65%	7 1/4	40	26	2	B	55.25	41.75
	65%	7 1/4	40	27	2	D	55.25	41.75
	65%	7 1/4	40	28	2	F	55.25	41.75
	65%	7 1/4	40	29	3	B	58.75	42.25
	65%	7 1/4	40	30	3	D	58.75	42.25
	65%	7 1/4	40	31	3	F	58.75	42.25
	65%	7 3/8	39 5/8	32	4	F	60.25	41.75

	Letoff %	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
PW ITNHW/V ITNTW/V	65/75	7	39 3/8	25	2	A	54.25	41.25
	65/75	7	39 3/8	26	2	C	54.25	41.25
	65/75	7	39 3/8	27	2	E	54.25	41.25
	65/75	7	39 3/8	28	2	G	54.25	41.25
	65/75	7	39 1/2	29	3	D	57.75	41.75
	65/75	7	39 1/2	30	3	F	57.75	41.75
	65/75	7	39 5/8	31	4	E	59.75	41.75
	65/75	7	39 5/8	32	4	G	59.75	41.75

W = 65%, V = 75%

Letoff, brace height, axle to axle length given as a general production guide only

Desc: TUNE/DEFLECTION CHART - INTEC CARBONITE HUNTING AND TARGET
 File: IT - TUNE: IT CARBONITE DATE: 14-Apr-99
 HOYT USA