

Model(s) **PROTEC**
Model Year **2003**
Limbs **XT2000**
Cable Guard Bar **9.50**
Limb Bolt Length **2.50**
Pocket **#22 or #23**

Date **3/17/2003**

Revision **G**

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	CAM & MODULE	MODULE POSITION	STRING	HCBC	HYBC
	65/75%	7 7/8	38 1/8	26	A-1	D	51.0	42.0	39.75
Cam	65/75%	8	37 7/8	27	B-2	D	52.0	42	39.75
&1/2	65/75%	8 1/8	38	28	C-3	D	52.5	42.25	39.75
Adjustable	65/75%	8	38 1/4	29	D-4	D	54.5	43	40.25
	65/75%	8 1/4	38	30	E-5	D	55.5	43.0	40.25
	65/75%	8 1/4	38 1/4	31	F-6	D	57.0	43.5	40.5
	65/75%	8 1/4	38 1/2	32	G-7	D	58.5	44.25	40.75

Cam / Wheel	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE
	65%	7 3/4	37 3/4	26.0	1.0	56.0	42.5	39.75
	65%	7 3/4	37 3/4	26.5	1.5	56.0	42.5	39.75
	65%	7 3/4	37 3/4	27.0	2.0	56.0	42.5	39.75
	65%	7 3/4	37 3/4	27.5	2.5	56.0	42.5	39.75
Spiral	65%	8	37 3/8	28.0	3.0	57.5	42.75	39.75
Cam	65%	8	37 3/8	28.5	3.5	57.5	42.75	39.75
&1/2	65%	8 1/8	36 7/8	29.0	4.5	58.5	42.0	38.75
	65%	8 1/8	36 7/8	29.5	5.0	58.5	42.0	38.75
	65%	8 1/8	36 7/8	30.0	5.5	58.5	42.0	38.75
	65%	8	37 1/2	30.5	6.0	60.5	42.5	39.5
	65%	8	37 1/2	31.0	6.5	60.5	42.5	39.5
	65%	8	37 1/2	31.5	7.0	60.5	42.5	39.5
	65%	8	37 3/4	32.5	7.5	62.5	43.5	39.5
	65%	8	37 3/4	33.0	8.0	62.5	43.5	39.5