

Model(s) Viper XT 2000 Hunting  
 Model Year 2000  
 Limbs XT 2000  
 Cable Guard Bar Carbon Med  
 Limb Bolt Length 2.5  
 Pocket 17

Date 1/25/2000  
 Revision A

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
AW V25HA	65%	5 3/8	34 1/4	19	1	A	46.25	36.25
	65%	5 3/8	34 1/4	20	1	C	46.25	36.25
	65%	5 3/8	34 1/4	21	1	F	46.25	36.25
	65%	5 3/8	34 3/8	22	2	B	48.25	36.25
	65%	5 3/8	34 3/8	23	2	E	48.25	36.25
	65%	5 3/8	34 3/8	24	2	G	48.25	36.25
	65%	5 3/8	34 3/4	25	3	B	52.75	36.75
	65%	5 3/8	34 3/4	26	3	E	52.75	36.75
	65%	5 3/8	34 3/4	27	3	G	52.75	36.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC V25HC/D	75 / 65%			20	1	A	46.25	35.75
	75 / 65%			21	1	C	46.25	35.75
	75 / 65%			22	1	E	46.25	35.75
	75 / 65%	5 1/2	34 3/8	23	2	B	49.25	36.25
	75 / 65%	5 1/2	34 3/8	24	2	C	49.25	36.25
	75 / 65%	5 1/2	34 3/8	25	2	F	49.25	36.25
	75 / 65%	5 5/8	34 3/8	26	3	B	52.75	36.75
	75 / 65%	5 5/8	34 3/8	27	3	D	52.75	36.75
	75 / 65%	5 5/8	34 3/8	28	3	G	52.75	36.75
	75 / 65%	5 5/8	34 3/4	29	4	F	55.25	37.25
75 / 65%	5 5/8	34 3/4	30	4	H	55.25	37.25	

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Buss Cable
R/S V25HR/S	65%	5 1/2	35	23	1	88.75	37.75
	65%	5 1/2	35	24	2	88.75	37.75
	65%	5 1/2	35	25	3	88.75	37.75
	75 / 65%	5 1/2	35	26	4	88.75	37.75
	75 / 65%	5 3/8	35 3/4	27	5	92.25	38.75
	75 / 65%	5 3/8	35 3/4	28	6	92.25	38.75
	75 / 65%	5 3/8	35 3/4	29	7	92.25	38.75
	75 / 65%	5 1/2	35 3/8	30	8	92.75	38.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Buss Cable
X V25HX	65%	5 7/8	33 1/8	23	1	45.25	34.75
	65%	5 7/8	33 1/2	24	2	46.75	35.25
	65%	5 3/4	34 1/8	25	3	48.75	35.75
	65%	5 7/8	33 7/8	26	4	49.25	35.75
	65%	5 3/4	34 3/8	27	5	51.25	35.75
	65%	5 7/8	34 1/2	28	6	52.75	35.75
	65%	5 1/2	35 1/8	29	7	54.75	36.75
	65%	5 1/2	35 1/2	30	8	56.25	36.75