

Model(s) UltraTec
Model Year 2004
Limbs XT2000
Cable Guard Bar 8 1/2
Limb Bolt Length 2 1/2
Pocket 25 & 26 High

Date 3/3/2004

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Cam/Module	Module Position	String	HCBC	HYBC
	65 / 75%	6 1/2	37 5/8	25	A-1	D	50.5	41.5	39.25
Cam	65 / 75%	6 5/8	37 5/8	26	B-2	D	51.5	41.75	39.5
&1/2	65 / 75%	6 3/4	37 3/8	27	C-3	D	52.5	41.75	39.25
Adjustable	65 / 75%	6 7/8	37 1/2	28	D-4	D	54.0	42.25	39.5
	65 / 75%	7	37 1/2	29	E-5	D	55.0	42.25	39.5
	65 / 75%	7 1/8	37 5/8	30	F-6	D	56.5	42.75	39.75
	65 / 75%	7 1/8	37 7/8	31	G-7	D	58.0	43.5	40.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Cam/Module	Module Position	String	Control Cable	Buss Cable
	65%	6 1/2	37	24.5	1	55.0	41.5	39.0
Wheel	65%	6 1/2	37	25	1.5	55.0	41.5	39.0
	65%	6 1/2	37	25.5	2	55.0	41.5	39.0
Cam	65%	6 1/2	37	26	2.5	55.0	41.5	39.0
&1/2	65%	6 3/4	36 5/8	26.5	3	56.5	41.75	38.75
Spiral	65%	6 3/4	36 5/8	27	3.5	56.5	41.75	38.75
	65%	6 3/4	36 5/8	27.5	4	56.5	41.75	38.75
	65%	6 3/4	36 3/4	28	4.5	58.5	41.75	38.5
	65%	6 3/4	36 3/4	28.5	5	58.5	41.75	38.5
	65%	6 3/4	36 3/4	29	5.5	58.5	41.75	38.5
	65%	6 3/4	37	29.5	6	60.0	41.75	38.75
	65%	6 3/4	37	30	6.5	60.0	41.75	38.75
	65%	6 3/4	37	30.5	7	60.0	41.75	38.75
	65%	6 3/4	37	31	7.5	61.5	42.5	38.5
	65%	6 3/4	37	31.5	8	61.5	42.5	38.5