

Model(s) Intensity Target & Hunting

Date 2-Nov-98

Model Year 1999

Limbs 4 Piece Glass 14"

Revision

Cable Guard Bar Short Double Bend

Limb Bolt Length 1.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
YC	70%	5 3/4	32 1/2	21	1	B	45.25	36.25
INYHY	70%	5 3/4	32 1/2	22	1	D	45.25	36.25
INYTY	70%	5 3/4	32 1/2	23	1	F	45.25	36.25
	70%	5 3/4	32 1/2	24	1	H	45.25	36.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
YS	65%	6 7/8	32 1/2	23	1	A	82.25	36.25
INYHU	65%	6 7/8	32 1/2	24	1	C	82.25	36.25
INYTU	65%	6 7/8	32 1/2	25	1	E	82.25	36.25
	65%	6 7/8	32 1/2	26	1	G	82.25	36.25

Letoff, brace height, axle to axle length given as a general production guide only

Desc: TUNE/DEFLECTION CHART - INTENSITY HUNTING AND TARGET

File: IN - TUNE: INTENSITY YOUTH LIMB DATE: 2-Nov-98

HOYT USA