

Model(s) UltraTec
Model Year 2004
Limbs XT3000
Cable Guard Bar 9 1/2
Limb Bolt Length 2 1/2
Pocket 25 & 26 High

Date 11/12/2003

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Cam / Module	Module Position	String	HCBC	HYBC
	65/75%	7 7/16	40 5/8	26	A-1	C	53.5	44.5	42.25
Cam	65/75%	7 3/8	40 1/2	27	B-2	C	54.5	44.75	42.5
&1/2	65/75%	7 9/16	40 7/16	28	C-3	C	55.5	44.75	42.25
Adjustable	65/75%	7 5/8	40 1/2	29	D-4	C	57.0	45.25	42.5
	65/75%	7 3/4	40 7/16	30	E-5	C	58.0	45.25	42.5
	65/75%	7 7/8	40 7/16	31	F-6	C	59.5	45.75	42.75
	65/75%	7 7/8	40 3/4	32	G-7	C	61	46.5	43.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Control Cable	Buss Cable
	65%	7 1/4	40	26	1	58.0	44.5	41.75
Cam	65%	7 1/4	40	26.5	1.5	58.0	44.5	41.75
&1/2	65%	7 1/4	40	27	2	58.0	44.5	41.75
Spiral	65%	7 1/4	40	27.5	2.5	58.0	44.5	41.75
	65%	7 1/2	39 1/2	28	3	59.5	44.5	41.5
	65%	7 1/2	39 1/2	28.5	3.5	59.5	44.5	41.5
	65%	7 1/2	39 1/2	29	4	59.5	44.5	41.5
	65%	7 1/2	39 3/4	29.5	4.5	61.5	44.75	41.5
	65%	7 1/2	39 3/4	30	5	61.5	44.75	41.5
	65%	7 1/2	39 3/4	30.5	5.5	61.5	44.75	41.5
	65%	7 1/2	39 7/8	31	6	63.0	44.5	41.5
	65%	7 1/2	39 7/8	31.5	6.5	63.0	44.5	41.5
	65%	7 1/2	39 7/8	32	7	63.0	44.5	41.5
	65%	7 1/2	39 7/8	32.5	7.5	64.5	45.25	41.25
	65%	7 1/2	39 7/8	33	8	64.5	45.25	41.25