

Model(s) Vortec XT 2000 Hunting
 Model Year 2001
 Limbs XT 2000 (15" Magum)
 Cable Guard Bar
 Limb Bolt Length 2.5

Date 7/13/2017
 Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	6 7/8	36	24.5	1	3	92.25	37.50
	60 / 75%	6 7/8	36	25	1.5	3	92.25	37.50
	60 / 75%	6 7/8	36	25.5	2	3	92.25	37.50
	60 / 75%	6 7/8	36	26	2.5	3	92.25	37.50
	60 / 75%	6 7/8	36	26.5	3	3	92.25	37.50
Saber	60 / 75%	6 7/8	36	27	3.5	3	92.25	37.50
	60 / 75%	7 1/8	36 1/4	27.5	4	4	94.75	38.00
B	60 / 75%	7 1/8	36 1/4	28	4.5	4	94.75	38.00
	60 / 75%	7 1/8	36 1/4	28.5	5	4	94.75	38.00
VT5HB	60 / 75%	7 1/8	36 1/4	29	5.5	4	94.75	38.00
	60 / 75%	7 1/8	36 1/4	29.5	6	4	94.75	38.00
	60 / 75%	7 1/8	36 1/4	30	6.5	4	94.75	38.00
	60 / 75%	7	36 5/8	30.5	7	5	97.75	38.50
	60 / 75%	7	36 5/8	31	7.5	5	97.75	38.50
	60 / 75%	7	36 5/8	31.5	8	5	97.75	38.50

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	6 3/8	35 3/8	21	1	A	47.75	37.00
	65%	6 3/8	35 3/8	22	1	C	47.75	37.00
Command	65%	6 3/8	35 3/8	23	1	E	47.75	37.00
C/D	65%	6 3/8	35 3/8	24	1	G	47.75	37.00
VT5HC/D	65 / 75%	6 1/4	35 7/8	25	2	D	50.75	37.50
	65 / 75%	6 1/4	35 7/8	26	2	F	50.75	37.50
	65 / 75%	6 1/2	35 5/8	27	3	C	54.25	38.00
	65 / 75%	6 1/2	35 5/8	28	3	E	54.25	38.00
	65 / 75%	6 1/2	35 5/8	29	3	G	54.25	38.00
	65 / 75%	6 1/4	36 1/2	30	4	E	57.25	38.50
	65 / 75%	6 1/4	36 1/2	31	4	G	57.25	38.50

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	Idler Wheel	String	Buss Cable
	60 / 75%	6 1/2	35 3/8	25	1	A-4	1	88.25	38.00
	60 / 75%	6 1/2	35 3/8	26	1	E-5	1	88.25	38.00
Versa	60 / 75%	6 1/2	35 7/8	27	2	A-3	2	92.25	38.50
V	60 / 75%	6 1/2	35 7/8	28	2	C-6	2	92.25	38.50
VT5HV	60 / 75%	6 1/2	35 7/8	29	2	F-8	2	92.25	38.50
	60 / 75%	6 1/2	36 1/4	30	3	D-6	2	96.25	39.00
	60 / 75%	6 1/2	36 1/4	31	3	F-8	2	96.25	39.00

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	6 1/2	35 5/8	24.5	1	1	89.25	39.00
	60 / 75%	6 1/2	35 5/8	25	1.5	1	89.25	39.00
	60 / 75%	6 1/2	35 5/8	25.5	2	1	89.25	39.00
	60 / 75%	6 1/2	35 5/8	26	2.5	1	89.25	39.00
	60 / 75%	6 1/2	35 5/8	26.5	3	1	89.25	39.00
Redline	60 / 75%	6 1/2	35 5/8	27	3.5	1	89.25	39.00
	60 / 75%	6 1/2	35 5/8	27.5	4	1	89.25	39.00
Z	60 / 75%	6 1/2	35 5/8	28	4.5	1	89.25	39.00
	60 / 75%			28.5	5	2	93.25	40.00
VT5HZ	60 / 75%			29	5.5	2	93.25	40.00
	60 / 75%			29.5	6	2	93.25	40.00
	60 / 75%			30	6.5	2	93.25	40.00
	60 / 75%			30.5	7	2	93.25	40.00
	60 / 75%	6 1/4	36 3/4	31	7.5	2	95.25	41.00
	60 / 75%	6 1/4	36 3/4	31.5	8	2	95.25	41.00