

Model(s) UltraElite
 Model Year 2006
 Limbs XT3000
 Cable Guard Bar 9 1/2
 Limb Bolt Length 2 1/2
 Pocket 31 & 32

Date 12/8/2005

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	7 7/16	41	27	E	C&1/2 #1	54.25	44.5	42.25
	65/75	7 1/2	41 1/16	28	E	C&1/2 #2	55.25	44.75	42.5
	65/75	7 7/16	41 1/4	29	E	C&1/2 #3	56.5	45.5	42.75
	65/75	7 3/8	41 1/4	30	E	C&1/2 #4	58	46	43.25
	65/75	7 3/8	41 3/8	31	E	C&1/2 #5	59.25	46.25	43.5
	65/75	7 7/16	41 1/2	32	E	C&1/2 #6	60.5	46.75	43.75
	65/75	7 9/16	41 1/2	33	E	C&1/2 #7	61.75	47.25	43.75

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	7 5/16	40 1/8	26	1.0	58.25	44.75	42
	65%	7 5/16	40 1/8	26 1/2	1.5	58.25	44.75	42
	65%	7 5/16	40 1/8	27	2.0	58.25	44.75	42
	65%	7 5/16	40 1/8	27 1/2	2.5	58.25	44.75	42
	65%	7 7/16	39 7/8	28	3.0	59.75	45	42
	65%	7 7/16	39 7/8	28 1/2	3.5	59.75	45	42
	65%	7 7/16	39 7/8	29	4.0	59.75	45	42
	65%	7 7/16	40 1/8	29 1/2	4.5	61.75	45	41.75
	65%	7 7/16	40 1/8	30	5.0	61.75	45	41.75
	65%	7 7/16	40 1/8	30 1/2	5.5	61.75	45	41.75
	65%	7 7/16	40 1/4	31	6.0	63.25	45	42
	65%	7 7/16	40 1/4	31 1/2	6.5	63.25	45	42
	65%	7 7/16	40 1/4	32	7.0	63.25	45	42
	65%	7 7/16	40 3/8	32 1/2	7.5	64.5	46	42
	65%	7 7/16	40 3/8	33	8.0	64.5	46	42

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable	
wheel & 1/2	65%	7 7/16	40 5/8	24 1/2	0.0	57	44.75	41.75	
	65%	7 7/16	40 5/8	25	0.5	57	44.75	41.75	
	65%	7 7/16	40 5/8	25 1/2	1.0	57	44.75	41.75	
	65%	7 7/16	40 5/8	26	1.5	57	44.75	41.75	
	65%	7 7/16	40 5/8	26 1/2	2.0	57	44.75	41.75	
	65%	7 7/16	40 5/8	27	2.5	57	45	41.75	
	65%	7 7/16	40 5/8	27 1/2	3.0	57	45	41.75	
	65%	7 5/8	40 1/2	28	3.5	60.75	46	42	
	65%	7 5/8	40 1/2	28 1/2	4.0	60.75	46	42	
	65%	7 5/8	40 1/2	29	4.5	60.75	46	42	
	65%	7 5/8	40 1/2	29 1/2	5.0	60.75	46	42	
	65%	7 5/8	40 1/2	30	5.5	60.75	46	42	
	165%	7 5/8	40 1/2	30 1/2	6.0	60.75	46	42	
	65%	7 3/4	40 3/4	31	6.5	65	47.5	42.75	
	65%	7 3/4	40 3/4	31 1/2	7.0	65	47.5	42.75	
	65%	7 3/4	40 3/4	32	7.5	65	47.5	42.75	
	2006% JUNE 01/04	65%	7 3/4	40 3/4	32 1/2	8.0	65	47.5	42.75