

Model(s) Striker Intruder Hunting Date 23-Apr-98
 Model Year 1998
 Limbs Solid Glass (16") Revision D
 Cable Guard Bar Medium
 Limb Bolt Length 2.25
 Physical Weight 4 lbs. 13 oz.

*****Draw Weight*****

CC
SKDHC

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable	40	50	60	70	80
75%	7 1/4	39 3/4	26	2	C	54.25	41.25	60	52	42	38	34
75%	7 1/4	39 3/4	27	2	E	54.25	41.25	60	52	42	38	34
75%	7 1/4	39 3/4	28	2	G	54.25	41.25	60	52	42	38	34
75%	7 1/4	39 3/4	29	3	B	57.75	41.75	66	56	46	40	34
75%	7 1/4	39 3/4	30	3	D	57.75	41.75	66	56	46	40	34
75%	7 1/4	39 3/4	31	3	F	57.75	41.75	66	56	46	40	34

*****Draw Weight*****

CC
SKDHC

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable	40	50	60	70	80
65%	7 1/4	39 3/4	26	2	C	54.25	41.25	60	52	42	38	34
65%	7 1/4	39 3/4	27	2	E	54.25	41.25	60	52	42	38	34
65%	7 1/4	39 3/4	28	2	G	54.25	41.25	60	52	42	38	34
65%	7 1/4	39 3/4	29	3	B	57.75	41.75	66	56	46	40	34
65%	7 1/4	39 3/4	30	3	D	57.75	41.75	66	56	46	40	34
65%	7 1/4	39 3/4	31	3	F	57.75	41.75	66	56	46	40	34

Letoff, brace height, axle to axle length given as a general production guide only

THIS DATA SHEET VOID FOR PRODUCTION USE UNLESS RELEASE STAMP APPEARS IN RED

Desc: TUNE/DEFLECTION CHART -STRIKER INTRUDER HUNTING

File: SK - TUNE: SK INTRUDER DATE: 23-Apr-98

HOYT USA