

Model(s) **ProTec**
 Model Year **2006**
 Limbs **XT2000**
 Cable Guard Bar **9 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **27 & 28**

Date **12/8/2005**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	7 1/2	38 1/8	26	E	C&1/2 #1	50.75	41.75	39.5
cam	65/75	7 5/8	38	27	E	C&1/2 #2	51.75	41.75	39.5
& 1/2	65/75	7 13/16	37 5/8	28	E	C&1/2 #3	52.5	42	39.25
adjustable	65/75	7 7/8	37 3/8	29	E	C&1/2 #4	53.75	42.25	39.5
	65/75	7 15/16	37 1/2	30	E	C&1/2 #5	55.25	42.5	39.75
	65/75	8 1/16	37 3/4	31	E	C&1/2 #6	56.5	43	40
	65/75	8 3/16	37 3/4	32	E	C&1/2 #7	57.75	43.5	40

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	7 3/8	37 1/2	25 1/2	1	55.25	42	39.25
	65%	7 3/8	37 1/2	26	1 1/2	55.25	42	39.25
	65%	7 3/8	37 1/2	26 1/2	2	55.25	42	39.25
	65%	7 3/8	37 1/2	27	2 1/2	55.25	42	39.25
	65%	7 5/8	37	27 1/2	3	56.75	42	39
	65%	7 5/8	37 1/16	28	3 1/2	56.75	42	39
cam	65%	7 5/8	37 1/16	28 1/2	4	56.75	42	39
& 1/2	65%	7 1/2	37 3/8	29	4 1/2	59	42.25	39
spiral	65%	7 1/2	37 3/8	29 1/2	5	59	42.25	39
	65%	7 1/2	37 3/8	30	5 1/2	59	42.25	39
	65%	7 5/8	37 3/8	30 1/2	6	60.5	42	39
	65%	7 5/8	37 3/8	31	6 1/2	60.5	42	39
	65%	7 5/8	37 3/8	31 1/2	7	60.5	42	39
	65%	7 5/8	37 1/2	32	7 1/2	62	43	39
	65%	7 5/8	37 1/2	32 1/2	8	62	43	39