

Model(s) UltraTec XT 2000 Target
 Model Year 2000
 Limbs XT 2000 (15" Magnum)
 Cable Guard Bar S/S 6.25
 Limb Bolt Length 2.5
 Pocket

Date 1/20/1999

Revision A

Pocket	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
#20	65%	6 3/8	38 5/8	22	1	A	51.25	40.25
	65%	6 3/8	38 5/8	23	1	C	51.25	40.25
CC UT5TC/D	65%	6 3/8	38 5/8	24	1	E	51.25	40.25
	75 / 65%	6 3/8	38 5/8	25	2	B	53.75	40.25
	75 / 65%	6 3/8	38 5/8	26	2	D	53.75	40.25
	75 / 65%	6 3/8	38 5/8	27	2	F	53.75	40.25
	75 / 65%	6 3/8	38 3/4	28	3	C	57.25	41.25
	75 / 65%	6 3/8	38 3/4	29	3	E	57.25	41.25
	75 / 65%	6 3/8	38 3/4	30	3	G	57.25	41.25
	75 / 65%	6 3/8	39	31	4	G	59.25	41.75
	75 / 65%	6 3/8	39	32	4	H	59.25	41.75

Pocket	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Zebra String	Buss Cable
#19	75 / 65%	6 5/8	38 1/2	25	1	95.75	41.25
	75 / 65%	6 5/8	38 1/2	26	2	95.75	41.25
R/S UT5TR/S	75 / 65%	6 5/8	38 1/2	27	3	95.75	41.25
	75 / 65%	6 5/8	38 1/2	28	4	95.75	41.25
	75 / 65%	6 5/8	38 1/2	29	5	98.25	41.75
	75 / 65%	6 5/8	38 1/2	30	6	98.25	41.75
	75 / 65%	6 5/8	38 1/2	31	7	98.25	41.75
	75 / 65%	6 5/8	38 7/8	32	8	99.75	42.25

Pocket	Letoff %	Brace Height	Axle to Axle	Draw Length	Base Cam	Zebra String	Buss Cable
#20	65%	7	36 1/8	25	1	48.75	38.25
	65%	6 7/8	37	26	2	50.25	38.75
	65%	6 3/4	37 5/8	27	3	52.25	39.25
X UT5TX	65%	6 7/8	37 1/2	28	4	52.75	39.25
	65%	6 7/8	37 7/8	29	5	54.75	39.75
	65%	6 5/8	38 5/8	30	6	56.75	40.25
	65%	6 5/8	38 5/8	31	7	58.25	40.25
	65%	6 1/2	39 1/2	32	8	60.25	41.25