

Model(s) ULTRATEC
Model Year 2003
Limbs XT2000
Cable Guard Bar 8.50
Limb Bolt Length 2.50
Pocket #22 or #23

Date 3/19/03
Revision I

| Cam / Wheel | LETOFF | BRACE HEIGHT | AXLE TO AXLE | DRAW LENGTH | CAM & MODULE | MODULE POSITION | STRING | HCBC | HYBC |
|-------------|--------|--------------|--------------|-------------|--------------|-----------------|--------|-------|-------|
| | 65/75% | 6 1/2 | 37 5/8 | 24 | A-1 | C | 50.5 | 41.5 | 39.25 |
| | 65/75% | 6 5/8 | 37 5/8 | 25 | B-2 | C | 51.5 | 41.75 | 39.5 |
| Cam | 65/75% | 6 7/8 | 37 3/8 | 26 | C-3 | C | 52.0 | 41.25 | 38.75 |
| &1/2 | 65/75% | 7 | 37 1/4 | 27 | D-4 | C | 53.5 | 42.0 | 39.25 |
| Adjustable | 65/75% | 7 1/8 | 37 1/4 | 28 | E-5 | C | 54.5 | 42.0 | 39.25 |
| | 65/75% | 7 | 37 3/4 | 29 | F-6 | C | 56.5 | 43.0 | 40.0 |
| | 65/75% | 7 | 38 | 30 | G-7 | C | 58.0 | 43.75 | 40.25 |

| Cam / Wheel | LETOFF | BRACE HEIGHT | AXLE TO AXLE | DRAW LENGTH | BASE CAM | STRING | HCBC | HYBC |
|-------------|--------|--------------|--------------|-------------|----------|--------|-------|-------|
| | 65% | 6 1/2 | 37 3/8 | 24.5 | 1 | 55.5 | 42.0 | 39.25 |
| | 65% | 6 1/2 | 37 3/8 | 25 | 1.5 | 55.5 | 42.0 | 39.25 |
| | 65% | 6 1/2 | 37 3/8 | 25.5 | 2 | 55.5 | 42.0 | 39.25 |
| Spiral | 65% | 6 1/2 | 37 3/8 | 26 | 2.5 | 55.5 | 42.0 | 39.25 |
| Cam | 65% | 6 5/8 | 36 7/8 | 26.5 | 3 | 57.0 | 42.25 | 39.25 |
| &1/2 | 65% | 6 5/8 | 36 7/8 | 27 | 3.5 | 57.0 | 42.25 | 39.25 |
| | 65% | 6 5/8 | 36 7/8 | 27.5 | 4 | 57.0 | 42.25 | 39.25 |
| | 65% | 7 | 36 3/8 | 28 | 4.5 | 58.0 | 41.5 | 38.25 |
| | 65% | 7 | 36 3/8 | 28.5 | 5 | 58.0 | 41.5 | 38.25 |
| | 65% | 7 | 36 3/8 | 29 | 5.5 | 58.0 | 41.5 | 38.25 |
| | 65% | 6 3/4 | 36 7/8 | 29.5 | 6 | 60.0 | 41.75 | 38.75 |
| | 65% | 6 3/4 | 36 7/8 | 30 | 6.5 | 60.0 | 41.75 | 38.75 |
| | 65% | 6 3/4 | 36 7/8 | 30.5 | 7 | 60.0 | 41.75 | 38.75 |
| | 65% | 6 5/8 | 37 1/4 | 31 | 7.5 | 62.0 | 43.0 | 39.0 |
| | 65% | 6 5/8 | 37 1/4 | 31.5 | 8 | 62.0 | 43.0 | 39.0 |