

Model(s) **ProTec**
 Model Year **2005**
 Limbs **XT2000**
 Cable Guard Bar **9 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **Triton #27&28**

Date **11/23/2004**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	7 3/8	38 1/4	26	D	A	51	42	39.75
	65/75	7 1/2	38	27	D	B	52	42.25	39.75
	65/75	7 5/8	38	28	D	C	53	42.25	39.75
	65/75	7 7/8	37 1/2	29	D	D	54	42.25	39.5
	65/75	7 7/8	37 7/8	30	D	E	55.5	42.75	40
	65/75	7 7/8	38 1/4	31	D	F	57	43.25	40.25
	65/75	7 7/8	38 3/8	32	D	G	58.5	44	40.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	7 3/8	37 3/8	25 1/2	1.0	55.5	42	39.5
	65%	7 3/8	37 3/8	26	1.5	55.5	42	39.5
	65%	7 3/8	37 3/8	26 1/2	2.0	55.5	42	39.5
	65%	7 3/8	37 3/8	27	2.5	55.5	42	39.5
	65%	7 1/2	37	27 1/2	3.0	57	42.25	39.25
	65%	7 1/2	37	28	3.5	57	42.25	39.25
	65%	7 1/2	37	28 1/2	4.0	57	42.25	39.25
	65%	7 1/2	37 1/8	29	4.5	59	42.25	39
	65%	7 1/2	37 1/8	29 1/2	5.0	59	42.25	39
	65%	7 1/2	37 1/8	30	5.5	59	42.25	39
	65%	7 5/8	37 3/8	30 1/2	6.0	60.5	42.25	39.25
	65%	7 5/8	37 3/8	31	6.5	60.5	42.25	39.25
	65%	7 5/8	37 3/8	31 1/2	7.0	60.5	42.25	39.25
	65%	7 5/8	37 1/2	32	7.5	62	43	39
	65%	7 5/8	37 1/2	32 1/2	8.0	62	43	39