

Model(s) Striker Carbon Plus 4 Target & Hunting

Date 28-Feb-98

Model Year 1998

Limbs 4 Piece Carbon Plus (18")

Revision B

Cable Guard Bar Medium

Limb Bolt Length 2.5

Physical Weight

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7 5/8	43 1/4	24	1	C	55.75	45.25
AW	65%	7 5/8	43 1/4	25	1	E	55.75	45.25
SK4HA	65%	7 5/8	43 1/4	26	2	D	57.25	45.25
SK4TA	65%	7 5/8	43 1/4	27	2	F	57.25	45.25
	65%	7 5/8	43 1/4	28	2	H	57.25	45.25
	65%	7 5/8	43 1/4	29	3	C	60.75	45.25
	65%	7 5/8	43 1/4	30	3	E	60.75	45.25
	65%	7 5/8	43 1/4	31	3	G	60.75	45.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	75%	7 1/2	43	27	2	B	57.75	44.75
CC	75%	7 1/2	43	28	2	D	57.75	44.75
SK4HC	75%	7 1/2	43	29	2	F	57.75	44.75
SK4TC	75%	7 1/2	43	30	2	H	57.75	44.75
	75%	7 1/2	43	31	3	C	61.75	45.25
	75%	7 1/2	43	32	3	E	61.75	45.25
	75%	7 1/2	43	33	3	G	61.75	45.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7 1/2	43	27	2	B	57.75	44.75
CC	65%	7 1/2	43	28	2	D	57.75	44.75
SK4HD	65%	7 1/2	43	29	2	F	57.75	44.75
SK4TD	65%	7 1/2	43	30	2	H	57.75	44.75
	65%	7 1/2	43	31	3	C	61.75	45.25
	65%	7 1/2	43	32	3	E	61.75	45.25
	65%	7 1/2	43	33	3	G	61.75	45.25

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*  
 THIS DATA SHEET VOID FOR PRODUCTION USE UNLESS RELEASE STAMP APPEARS IN RED

Desc: TUNE/DEFLECTION CHART - STIKER CARBON PLUS 4 TARGET & HUNTING  
 File: SK - TUNE: SK CARBON PLUS 4 DATE: 28-Feb-98  
 HOYT USA