

Model(s) **ProElite**
 Model Year **2005**
 Limbs **XT4000**
 Cable Guard Bar **10 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **Triton #25&26**

Date **1/26/05**

Revision **B**

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	8 5/8	46	29	D	A	59	49.75	47.5
	65/75	8 3/4	45 3/4	30	D	B	60	50.25	48
	65/75	8 7/8	46	31	D	C	61	50.25	47.75
	65/75	8 7/8	45 7/8	32	D	D	62	50.5	47.75
	65/75	9 1/8	46	33	D	E	63.5	50.75	48
	65/75	9 1/8	45 7/8	34	D	F	65	51.25	48.25
	65/75	9 1/8	46	35	D	G	66.5	52	48.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	9 1/4	45 1/4	27 1/2	0.0	61.5	49.25	46.25
	65%	9 1/4	45 1/4	28	0.5	61.5	49.25	46.25
	65%	9 1/4	45 1/4	28 1/2	1.0	61.5	49.25	46.25
	65%	9 1/4	45 1/4	29	1.5	61.5	49.25	46.25
	65%	9 1/4	45 1/4	29 1/2	2.0	61.5	49.25	46.25
	65%	9 1/4	45 1/4	30	2.5	61.5	49.5	46.25
	65%	9 1/4	45 1/4	30 1/2	3.0	61.5	49.5	46.25
	65%	9 3/8	45	31	3.5	65.5	50.5	46.5
	65%	9 3/8	45	31 1/2	4.0	65.5	50.5	46.5
	65%	9 3/8	45	32	4.5	65.5	50.5	46.5
	65%	9 3/8	45	32 1/2	5.0	65.5	50.5	46.5
	65%	9 3/8	45	33	5.5	65.5	50.5	46.5
	65%	9 3/8	45 1/2	33 1/2	6.5	70	52	47.25
	65%	9 3/8	45 1/2	34	7.0	70	52	47.25
	65%	9 3/8	45 1/2	34 1/2	7.5	70	52	47.25
	65%	9 3/8	45 1/2	35	8.0	70	52	47.25