

Model(s) **Katera**
Model Year **2008**
Limbs **XT500**
Cable Guard Bar **7 1/2**
Stealth shot bar **5**
Limb Bolt Length **2 1/2**
Pocket **31 & 32**

Date **11/26/2007**
Revision

**Z3
Cam**

| % Letoff | Brace Height | Axle to Axle | Draw Length | Base Cam | String | control cable | buss cable |
|-------------|-----------------|-----------------|----------------|-------------|--------|------------------|---------------|
| 65/75 | 5 3/4 | 32 2/3 | 23 1/2 | 0.5 | 48.25 | 37.50 | 34.50 |
| 65/75 | 5 3/4 | 32 1/4 | 24 | 1.0 | 48.25 | 37.50 | 34.50 |
| 65/75 | 5 3/4 | 32 1/4 | 24 1/2 | 1.5 | 48.25 | 37.50 | 34.50 |
| 65/75 | 6 | 32 1/2 | 25 | 2.0 | 50.25 | 37.75 | 34.75 |
| 65/75 | 5 7/8 | 32 4/7 | 25 1/2 | 2.5 | 50.25 | 37.75 | 34.75 |
| 65/75 | 5 3/4 | 32 1/2 | 26 | 3.0 | 50.25 | 37.75 | 34.75 |
| 65/75 | 5 7/8 | 33 | 26 1/2 | 3.5 | 52.75 | 38.25 | 35.25 |
| 65/75 | 5 3/4 | 33 | 27 | 4.0 | 52.75 | 38.25 | 35.25 |
| 65/75 | 5 3/4 | 33 | 27 1/2 | 4.5 | 52.75 | 38.25 | 35.25 |
| 65/75 | 5 3/4 | 33 1/2 | 28 | 5.0 | 55.50 | 39 | 36 |
| 65/75 | 6 | 33 1/2 | 28 1/2 | 5.5 | 55.50 | 39 | 36 |
| 65/75 | 6 | 33 1/2 | 29 | 6.0 | 55.50 | 39 | 36 |
| 65/75 | 5 7/8 | 33 5/8 | 29 1/2 | 6.5 | 58 | 39.25 | 36.25 |
| 65/75 | 6 | 33 1/2 | 30 | 7.0 | 58 | 39.25 | 36.25 |