

Model(s) Sapphire XT 2000 Target
 Model Year 2000
 Limbs XT 2000 (15" Magnum)
 Cable Guard Bar Med
 Limb Bolt Length 2.5
 Pocket 20 & 19

Date 12/30/1999

Revision

| Pocket #20 | Letoff | Brace Height | Axle to Axle | Draw Length | Base Cam | Module Position | String | Buss Cable |
|------------|--------|--------------|--------------|-------------|----------|-----------------|--------|------------|
| | 65% | 6 1/2 | 34 3/8 | 21 | 1 | B | 46.75 | 36.25 |
| | 65% | 6 1/2 | 34 3/8 | 22 | 1 | D | 46.75 | 36.25 |
| AW | 65% | 6 1/2 | 34 3/8 | 23 | 2 | B | 48.25 | 36.25 |
| SA5TA | 65% | 6 1/2 | 34 3/8 | 24 | 2 | D | 48.25 | 36.25 |
| | 65% | 6 1/2 | 34 3/8 | 25 | 2 | F | 48.25 | 36.25 |
| | 65% | 6 7/8 | 33 3/4 | 26 | 3 | D | 51.25 | 36.25 |
| | 65% | 6 7/8 | 33 3/4 | 27 | 3 | F | 51.25 | 36.25 |
| | 65% | 6 7/8 | 33 3/4 | 28 | 3 | H | 51.25 | 36.25 |

| Pocket #20 | Letoff | Brace Height | Axle to Axle | Draw Length | Base Cam | Module Position | String | Buss Cable |
|------------|----------|--------------|--------------|-------------|----------|-----------------|--------|------------|
| | 65% | 6 5/8 | 33 7/8 | 21 | 1 | A | 46.25 | 35.75 |
| | 65% | 6 5/8 | 33 7/8 | 22 | 1 | C | 46.25 | 35.75 |
| CC | 65% | 6 5/8 | 33 7/8 | 23 | 1 | E | 46.25 | 35.75 |
| SA5TC/D | 75 / 65% | 6 5/8 | 33 7/8 | 24 | 2 | B | 49.25 | 36.25 |
| | 75 / 65% | 6 1/2 | 34 3/8 | 25 | 2 | D | 49.25 | 36.25 |
| | 75 / 65% | 6 1/2 | 34 3/8 | 26 | 2 | F | 49.25 | 36.25 |
| | 75 / 65% | 6 3/4 | 34 3/8 | 27 | 3 | B | 52.75 | 36.75 |
| | 75 / 65% | 6 3/4 | 34 3/8 | 28 | 3 | D | 52.75 | 36.75 |

| Pocket #19 | Letoff | Brace Height | Axle to Axle | Draw Length | Base Cam | Zebra String | Buss Cable |
|------------|----------|--------------|--------------|-------------|----------|--------------|------------|
| | 75 / 65% | 6 1/2 | 34 1/4 | 24 | 1 | 87.25 | 37.25 |
| R/S | 75 / 65% | 6 1/2 | 34 1/4 | 25 | 2 | 87.25 | 37.25 |
| SA5TR/S | 75 / 65% | 6 1/2 | 34 1/4 | 26 | 3 | 87.25 | 37.25 |
| | 75 / 65% | 6 1/2 | 34 1/4 | 27 | 4 | 87.25 | 37.25 |
| | 75 / 65% | 6 3/4 | 34 1/2 | 28 | 5 | 90.25 | 37.75 |

| Pocket #20 | Letoff | Brace Height | Axle to Axle | Draw Length | Base Cam | Zebra String | Buss Cable |
|------------|--------|--------------|--------------|-------------|----------|--------------|------------|
| | 65% | 6 7/8 | 33 1/8 | 24 | 1 | 45.25 | 34.75 |
| | 65% | 6 7/8 | 33 1/2 | 25 | 2 | 46.75 | 35.25 |
| X | 65% | 6 3/4 | 34 1/8 | 26 | 3 | 48.75 | 35.75 |
| SA5TX | 65% | 6 7/8 | 34 | 27 | 4 | 49.25 | 35.75 |
| | 65% | 6 3/4 | 34 3/8 | 28 | 5 | 51.25 | 36.25 |
| | 65% | | | | | | |