

**Model(s)** UltraElite  
**Model Year** 2004  
**Limbs** XT2000  
**Cable Guard Bar** 8 1/2  
**Limb Bolt Length** 2 1/2  
**Pocket** 27 & 28 Low

Date 1/26/2004

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Cam / Module	Module Position	String	HCBC	HYBC
	65 / 75%	6 1/2	38 1/4	25	A-1	D	51.0	42.0	39.75
Cam	65 / 75%	6 5/8	38 1/4	26	B-2	D	52.0	42.25	40.0
&1/2	65 / 75%	6 7/8	38	27	C-3	D	53.0	42.25	39.75
Adjustable	65 / 75%	7	38	28	D-4	D	54.5	43.0	40.25
	65 / 75%	7	38	29	E-5	D	55.5	42.75	40.0
	65 / 75%	7 1/8	38 1/8	30	F-6	D	57.0	43.25	40.25
	65 / 75%	7 1/4	38 3/8	31	G-7	D	58.5	44.0	40.5

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Control Cable	Buss Cable
Cam / Wheel	65%	6 3/4	37	24.5	1	55.0	41.5	39.0
	65%	6 3/4	37	25	1.5	55.0	41.5	39.0
	65%	6 3/4	37	25.5	2	55.0	41.5	39.0
Cam	65%	6 3/4	37	26	2.5	55.0	41.5	39.0
&1/2	65%	7	36 5/8	26.5	3	56.5	41.75	38.75
Spiral	65%	7	36 5/8	27	3.5	56.5	41.75	38.75
	65%	7	36 5/8	27.5	4	56.5	41.75	38.75
	65%	6 7/8	37	28	4.5	58.5	42.0	38.75
	65%	6 7/8	37	28.5	5	58.5	42.0	38.75
	65%	6 7/8	37	29	5.5	58.5	42.0	38.75
	65%	6 3/4	37 1/2	29.5	6	60.5	42.25	39.25
	65%	6 3/4	37 1/2	30	6.5	60.5	42.25	39.25
	65%	6 3/4	37 1/2	30.5	7	60.5	42.25	39.25
	65%	7	37	31	7.5	61.5	42.5	38.5
	65%	7	37	31.5	8	61.5	42.5	38.5