

Model(s) UltraTec II XT 2000 TARGET
 Model Year 2001
 Limbs XT 2000 (15" Magnum)
 Cable Guard Bar
 Limb Bolt Length 2.25
 Pocket

Date 3/22/2001

Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
		65%	6 3/4	38 1/8	22	1	C	50.5
AccuWheel	65%	6 3/4	38 1/8	23	1	E	50.5	40.5
	65%	6 3/4	38 3/8	24	2	B	52.5	40.5
A	65%	6 3/4	38 3/8	25	2	D	52.5	40.5
	65%	6 3/4	38 3/8	26	2	G	52.5	40.5
U25TA	65%	6 3/4	38 3/8	27	3	C	56.5	41.0
	65%	6 3/4	38 3/8	28	3	F	56.5	41.0
	65%	6 3/4	38 3/8	29	3	H	56.5	41.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
					25.5	1	3	97.5
	60 / 75%	7 1/2	38 3/8	26	1.5	3	97.5	40.5
				26.5	2	3	97.5	40.5
Saber	60 / 75%	7 1/2	38 3/8	27	2.5	3	97.5	40.5
				27.5	3	3	97.5	40.5
B	60 / 75%	7 1/2	38 3/8	28	3.5	3	97.5	40.5
				28.5	4	4	100.0	41.0
U25TB	60 / 75%	7 3/4	38 3/8	29	4.5	4	100.0	41.0
				29.5	5	4	100.0	41.0
	60 / 75%	7 3/4	38 3/8	30	5.5	4	100.0	41.0
				30.5	6	4	100.0	41.0
	60 / 75%	7 3/4	38 3/8	31	6.5	4	100.0	41.0
				31.5	7	5	103.0	41.5
	60 / 75%	7 5/8	39 1/8	32	7.5	5	103.0	41.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
		65%	6 3/4	38 1/4	22	1	A	51.0
	65%	6 3/4	38 1/4	23	1	C	51.0	40.5
	65%	6 3/4	38 1/4	24	1	E	51.0	40.5
Command	65%	6 3/4	38 1/4	25	1	G	51.0	40.5
	65 / 75%	6 7/8	38 1/2	26	2	D	53.5	40.5
C/D	65 / 75%	6 7/8	38 1/2	27	2	F	53.5	40.5
	65 / 75%	6 3/4	38 7/8	28	3	B	57.5	41.5
U25TC/D	65 / 75%	6 3/4	38 7/8	29	3	D	57.5	41.5
	65 / 75%	6 3/4	38 7/8	30	3	F	57.5	41.5
	65 / 75%	6 1/2	39 7/8	31	4	D	61.0	42.0
	65 / 75%	6 1/2	39 7/8	32	4	F	61.0	42.0
	65 / 75%	6 1/2	39 7/8	33	4	H	61.0	42.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Buss Cable
		65%	6 7/8	38 1/4	26	1.5	52.0
	65%	6 7/8	38 1/4	26.5	2	52.0	40.0
	65%	7	38	27	2.5	53.0	40.0
Master X	65%	7	38	27.5	3	53.0	40.0
	65%	6 7/8	38 3/8	28	3.5	54.0	40.5
U25TX	65%	6 7/8	38 3/8	28.5	4	54.0	40.5
	65%	6 3/4	38 7/8	29	4.5	56.0	41.0
	65%	6 3/4	38 7/8	29.5	5	56.0	41.0
	65%	6 3/4	39 1/8	30	5.5	57.5	41.0
	65%	6 3/4	39 1/8	30.5	6	57.5	41.0
	65%	6 7/8	39 1/4	31	6.5	59.0	41.0
	65%	6 7/8	39 1/4	31.5	7	59.0	41.0
	65%	6 3/4	39 1/4	32	7.5	60.5	41.5
	65%	6 3/4	39 1/4	32.5	8	60.5	41.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
		60 / 75%	6 7/8	38 3/8	25.5	1	1	95.5
	60 / 75%	6 7/8	38 3/8	26	1.5	1	95.5	42.5
	60 / 75%	6 7/8	38 3/8	26.5	2	1	95.5	42.5
	60 / 75%	6 7/8	38 3/8	27	2.5	1	95.5	42.5
	60 / 75%	6 7/8	38 3/8	27.5	3	1	95.5	42.5
Redline Z	60 / 75%	6 7/8	38 3/8	28	3.5	1	95.5	42.5
	60 / 75%	6 7/8	38 3/8	28.5	4	1	95.5	42.5
U25TZ	60 / 75%	6 7/8	38 3/8	29	4.5	1	95.5	42.5
	60 / 75%			29.5	5	2	99.5	43.5
	60 / 75%			30	5.5	2	99.5	43.5
	60 / 75%			30.5	6	2	99.5	43.5
	60 / 75%			31	6.5	2	99.5	43.5
	60 / 75%			31.5	7	2	99.5	43.5
	60 / 75%	6 5/8	39 5/8	32	7.5	2	101.5	44.5
	60 / 75%	6 5/8	39 5/8	32.5	8	2	101.5	44.5