

Model(s) Deviator Power Flex Hunting
Model Year 1998
Limbs 4 Piece Flat Glass (16")
Cable Guard Bar Medium
Limb Bolt Length 2.5
Physical Weight 4 lbs 12 oz.

Date 20-Nov-97

Revision A

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC DVPHC	75%	5 1/2	39 3/4	25	2	D	55	35.5
	75%	5 1/2	39 3/4	26	2	F	55	35.5
	75%	5 1/2	39 3/4	27	2	H	55	35.5
	75%	5 1/2	39 3/4	28	3	D	58.5	36
	75%	5 1/2	39 3/4	29	3	F	58.5	36
	75%	5 1/2	39 3/4	30	3	H	58.5	36

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC DVPHD	65%	5 1/2	39 3/4	25	2	D	55	35.5
	65%	5 1/2	39 3/4	26	2	F	55	35.5
	65%	5 1/2	39 3/4	27	2	H	55	35.5
	65%	5 1/2	39 3/4	28	3	D	58.5	36
	65%	5 1/2	39 3/4	29	3	F	58.5	36
	65%	5 1/2	39 3/4	30	3	H	58.5	36

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
PC DVPHP	65%	5 1/2	39 1/2	25	2	D	56	35.5
	65%	5 1/2	39 1/2	26	2	F	56	35.5
	65%	5 1/2	39 1/2	27	2	H	56	35.5
	65%	5 1/2	39 1/2	28	3	D	60	36
	65%	5 1/2	39 1/2	29	3	F	60	36
	65%	5 1/2	39 1/2	30	3	H	60	36

Letoff, brace height, axle to axle length given as a general production guide only

THIS DATA SHEET VOID FOR PRODUCTION USE UNLESS RELEASE STAMP APPEARS IN REC

Desc: TUNE/DEFLECTION CHART - DEVIATOR POWER FLEX HUNTING

File: DV - TUNE: DV POWER FLEX

DATE:

20-Nov-97

HOYT USA