

Model(s) Mystic Contender Hunting & Target
 Model Year 1999
 Limbs Contender
 Cable Guard Bar Single Bend
 Limb Bolt Length 2.5

Date 23-Apr-99

Revision B

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
AW	65%	8 1/2	44	25	1	B	56.25	45.75
MYOHA	65%	8 1/2	44	26	1	D	56.25	45.75
MYOTA	65%	8 5/8	43 7/8	27	2	B	57.75	45.75
	65%	8 5/8	43 7/8	28	2	D	57.75	45.75
	65%	8 5/8	43 7/8	29	2	F	57.75	45.75
	65%	8 7/8	43 5/8	30	3	B	61.25	45.75
	65%	8 7/8	43 5/8	31	3	D	61.25	45.75
	65%	8 7/8	43 5/8	32	3	F	61.25	45.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC	75%	8 7/8	43 1/2	28	2	A	58.25	45.25
	75%	8 7/8	43 1/2	29	2	C	58.25	45.25
MYOHC	75%	8 7/8	43 1/2	30	2	E	58.25	45.25
MYOTC	75%	8 7/8	43 1/2	31	2	G	58.25	45.25
	75%	9	43 5/8	32	3	C	61.75	45.75
	75%	9	43 5/8	33	3	E	61.75	45.75

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
CC	65%	8 7/8	43 1/2	28	2	A	58.25	45.25
	65%	8 7/8	43 1/2	29	2	C	58.25	45.25
MYOHD	65%	8 7/8	43 1/2	30	2	E	58.25	45.25
MYOTD	65%	8 7/8	43 1/2	31	2	G	58.25	45.25
	65%	9	43 5/8	32	3	C	61.75	45.75
	65%	9	43 5/8	33	3	E	61.75	45.75

Letoff, brace height, axle to axle length given as a general production guide only

Desc: TUNE/DEFLECTION CHART - MYSTIC CONTENDER HUNTING & TARGET
 File: MY - TUNE: MY CONTENDER DATE: 23-Apr-99
 HOYT USA