

**Model(s)** MT Sport ZR 200 Hunting and Target  
**Model Year** 2002  
**Limbs** ZR 200  
**Cable Guard Bar** 10.50  
**Limb Bolt Length** 2.5  
**Pocket** 17

Date 11/20/2001

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65%	7 3/4	34 5/8	22	1	A	47.0	36.5
AccuWheel	65%	7 3/4	34 5/8	23	1	D	47.0	36.5
AW	65%	7 7/8	34 1/2	24	2	B	48.5	36.5
2MSZH/T	65%	7 7/8	34 1/2	25	2	D	48.5	36.5
	65%	7 7/8	34 1/2	26	2	H	48.5	36.5
	65%	8 1/8	34 3/4	27	3	B	52.5	37.0
	65%	8 1/8	34 3/4	28	3	E	52.5	37.0
	65%	8 1/8	34 3/4	29	3	G	52.5	37.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
	65 / 75%	8 1/8	34 5/8	22	1	A	47.5	35.5
Command	65 / 75%	8 1/8	34 5/8	23	1	C	47.5	35.5
CL/CH	65 / 75%	8 1/8	34 5/8	24	1	E	47.5	35.5
2MSZH/T	65 / 75%	8 1/8	34 5/8	25	1	G	47.5	35.5
	65 / 75%	8 1/4	34 3/4	26	2	C	50.0	35.5
	65 / 75%	8 1/4	34 3/4	27	2	E	50.0	35.5
	65 / 75%	8 1/4	34 3/4	28	2	G	50.0	35.5
	65 / 75%	8 5/8	34 7/8	29	3	C	54.0	35.5
	65 / 75%	8 5/8	34 7/8	30	3	E	54.0	35.5
	65 / 75%	8 3/8	35 3/8	31	4	D	57.5	36.0
	65 / 75%	8 3/8	35 3/8	32	4	F	57.5	36.0
	65 / 75%	8 3/8	35 3/8	33	4	H	57.5	36.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
	60 / 75%	8 1/2	34 5/8	26	1	B-2	3	54.0	40.5	37.5
Versa	60 / 75%	8 1/2	34 5/8	27	1	D-4	3	54.0	40.5	37.5
VC	60 / 75%	8 1/2	34 5/8	28	1	G-7	3	54.0	40.5	37.5
2MSZH/T	60 / 75%	8 3/4	34 3/8	29	2	E-5	4	56.0	41.5	37.5
	60 / 75%	8 3/4	34 3/8	30	2	G-7	4	56.0	41.5	37.5
	60 / 75%	9	34 5/8	31	3	C-3	5	60.0	42.0	38.0
	60 / 75%	9	34 5/8	32	3	E-5	5	60.0	42.0	38.0
	60 / 75%	9	34 5/8	33	3	G-7	5	60.0	42.0	38.0

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*